

TECHNICAL DATASHEET		
EGGER PRO LAMINATE FLOORING		8/ 31 Classic
Coreboard		HDF swell stopp plus
Profile		The patented EGGER installation system JUST clic! stands for quick and simple installation process without glue. Patented as JUST clic! EP 1 441 087 and EP 1 462 587
Guarantee domestic area		according to Egger Guarantee
Guarantee comercial area		according to Egger Guarantee
Antistatic properties according EN1815		yes, < 2 kV
Class of use	31	
European Norm EN13329		
Format	CLASSIC	
Dimension mm (length x width)	1292 x 192	
Complete thickness	8	
Thickness of silenizio® special cellulose		
Bevel	-	
Packaging		
Pallet	One-way-pallet	
Paket information		
	Piece	8
	m2	1,98
	kg	14,46
Pallet information		
	Piece	480
	m2	119,07
	kg	877,00
Classification and general requirements according EN13329		
Abrasion resistance according EN13329, annex E	AC3 (IP ≥ 2000)	
Impact resistance according EN13329, annex H	Big ball: ≥ 500 mm Small ball: ≥ 8 N	
Resistance to staining EN438	Group 1 + 2: level 5 group 3: level 4	
Effect of furniture leg according EN424	No damage shall be visible, when tested with foot Type 0 artefact	
Effect of a castor chair according EN425 (Type W)	No change in appearance or damage	
Thickness swelling according ISO 24336	≤ 18 %	
Tolerance of top layer according EN13329	length ± 0,5 mm width ± 0,1 mm	
Light fastness according EN13329	grey scale ≥ level 4 (EN:20105-A02)	
Static indentation by constant pressure according EN ISO 24343-1	< 0,05	
Surface soundness according EN13329, annex D	≥ 1,0 N/mm2	
Thermal resistance according to EN 12667	0,07 m² K/W	

