

TECHNICAL DATASHEET

EGGER PRO LAMINATE FLOORING

12/32 Classic WV4 Aqua+ CLIC it!

Core board	E1 HCHO	HDF Aqua Plus	
Locking system		The CLIC it! installation system means flexible and secure installation.	
Warranty time residential areas		Limited lifetime residential warranty according to the warranty declaration of EGGER Flooring International GmbH & Co.KG	
Warranty time commercial areas		5 years limited commercial warranty according to the warranty declaration of EGGER Flooring International GmbH & Co. KG	
Antistatic properties according to EN1815		yes, ≤ 2 kV	
Class of use	32		
European Standard EN13329			
Format	CLASSIC		
	1291 x 193 mm / 50.83 x 7.60 inch		
Overall thickness	12 mm		
Bevel	WV4 (4-sided bevel)		
Pallet	Packaging		
Paket information	One-way-pallet		
	Planks per Box	6	
	m ² / ft ²	1,50 / 16.09	
	kg / lbs	16,31/35.96	
Pallet information			
	Planks per Pallet	312	
	m ² / ft ²	77,73885 / 836.79	
	kg / lbs	860 / 1895.98	
	Classification and general requirements according EN13329		
Abrasion Resistance according to EN13329 (annex E)	AC4 (IP ≥ 4000)		
Impact resistance according to EN13329 (annex H)	Big ball: ≥ 750 mm / ≥ 29.53 inch Small ball: ≥ 12 N		
Resistance according to EN438	Group 1 + 2: level 5 group 3: level 4		
Effect of furniture leg according to EN424	No damage shall be visible, when tested with foot Type 0 artefact		
Effect of a castor chair according to EN425 (Type W)	No change in appearance or damage		
Thickness swelling according to ISO 24336	≤ 5 % (±1%)		
Tolerance of surface layer according to EN13329	length ± 0,5 mm / ± 0.019 inch width ± 0,1 mm / ± 0.0039 inch		
Tolerance of the thickness of the element according to EN13329	thickness ± 0,5 mm / ± 0.019 inch		
Light fastness according to EN13329	gray scale ≥ level 4 (EN:20105-A02)		
Static indentation by constant pressure according to EN ISO 24343-1	≤ 0.05		
Surface soundness according to EN13329, annex D	≥ 1.25 N/mm ² / ≥ 0.0019 inch ²		
Thermal resistance according to EN12667	~ 0.09 m ² K/W		
Slip resistance according to EN13893	<u>DS</u>		
Fire classification according to ASTM E648	Class 1		



WARNING: This product can expose you to chemicals including Formaldehyde which is known to the State of California to cause cancer. For more information go to HYPERLINK: www.P65Warnings.ca.gov
Drilling, sawing or machining wood products generates wood dust, a substance known to cause cancer. Avoid inhaling wood dust or use a NIOSH-approved half-mask respirator, side shielded safety glasses and other safeguards for personal protection.

