

TECHNICAL DATASHEET	
EGGER PRO COMFORT	
Large	
Coreboard	HDF swell stopp plus
Profil	The patented UNI fit! installation system stands for a quick and simple installation process without glue. Produced under the licence of Flooring Industries™.
Guarantee domestic area	according to Egger Guarantee
Guarantee comercial area	according to Egger Guarantee
Antistatic properties according EN1815	not available
Class of use	31
European Norm	EN 16511-31
Format	Large
Dimension mm (length x width)	1292 x 245
Complete thickness	10
Integrated underlay	yes, made from natural cork
Bevel	WW4
Packaging	
Pallet	One-way-pallet
Paket information	
Piece	7
m2	2,21
kg	18,09
Pallet information	
Piece	273
m2	86,19
kg	725,00
Classification and general requirements according to EN16511:2014	
abrasion resistance according EN13329, Annex E	IP ≥ 600 cycles
impact resistance according EN13329, Annex F	≥ 800 mm
resistance to staining EN 438 - 2	group 1 + 2: level 4 group 3: level 3
Thickness swelling according ISO 24336	≤ 20 %
tolerance of top layer according ISO 24337	length ± 0,5 mm width ± 0,1 mm thickness ± 0,5 mm
Static indentation by constant pressure according EN24343-1 (EN/ISO)	≤ 0,3
Effect of a castor chair according EN425	10.000 cycles
Thermal resistance according to EN 12667	0,09m2 K/W
Impact Sound Reduction according to EN ISO 10140 - 3	≤16 dB
Room Sound Reduction IHD W 431	43% (1)

* reference flooring construction: 7 mm laminate flooring on 3 mm PE-Foam and 0,2 mm PE-Film
The determined room sound improvement gives the percentage reduction of the loudness feeling relating to the reference.

