

TECHNICAL DATASHEET		
EGGER PRO LAMINATE FLOORING		10/32 Medium
Coreboard		HDF swell stopp plus
Profile		The patented UNI fit! installation system stands for a quick and simple installation process without glue. Produced under the licence of Flooring Industries™.
Guarantee domestic area		according to Egger Guarantee
Guarantee comercial area		according to Egger Guarantee
Antistatic properties according EN1815		yes, < 2 kV
Class of use		
European Norm EN13329		
Format	CLASSIC	
Dimension mm (length x width)	1291 x 135	
Complete thickness	10	
Thickness of silenzio® special cellulose		
Bevel	WV4	
Pallet	Packaging	
Pallet	One-way-pallet	
<b>Paket information</b>		
	Piece	7
	m2	1,22
	kg	11,24
<b>Pallet information</b>		
	Piece	490
	m2	85,40
	kg	805,14
Classification and general requirements according EN13329		
Abrasion resistance according EN13329, annex E	AC4 (IP ≥ 4000)	
Impact resistance according EN13329, annex H	Big ball: ≥ 750 mm Small ball: ≥ 12 N	
Resistance to staining EN438	Group 1 + 2: level 5 group 3: level 4	
Effect of furniture leg according EN424	No damage shall be visible, when tested with foot Type 0 artefact	
Effect of a castor chair according EN425 (Type W)	No change in appearance or damage	
Thickness swelling according ISO 24336	≤ 18 %	
Tolerance of top layer according EN13329	length ± 0,5 mm width ± 0,1 mm thickness ± 0,5 mm	
Light fastness according EN13329	grey scale ≥ level 4 (EN:20105-A02)	
Static indentation by constant pressure according EN ISO 24343-1	< 0,05	
Surface soundness according EN13329, annex D	≥ 1,25 N/mm2	
Thermal resistance according to EN 12667	0,08 m² K/W	

