



Declaration of Performance

According to the regulation (EU) Nr. 305 of the European Parliaments and of the Council of 09. March 2011

DOP No.: DOP183

1. Type:

Particle board Type: P2

2. Recipe no.:

Rec. 183

3. Intended use:

Boards for interior fitments (including furniture) for use in dry conditions

4. Trade name

EUROSPAN® E1 EPF-S CARB2 RF P2

5. Manufacturer:

EGGER Panneaux & Décors
Usine de Rion des Landes
Avenue d'Albret – BP 1
40371 Rion des Landes Cedex 01
France

SC EGGER România SRL
Str. Austriei 2
PO Box 38
725400 Radauti, jud. Suceava
Romania

6. System of assessment and verification acc. to Annex V of regulation (EU) No 305/2011:

System 4

7. Construction product covered by :

EN 13986

8. Notified body of the EU:

0765
Wilhelm-Klauditz-Institut (WKI)
Bienroder Weg 54 e
38108 Braunschweig
Germany

9. Declared Performance:

Mechanical properties	Unit	Board thickness					
	[mm]	6 -13	13 - 20	20 - 25	25 - 32	32 - 40	
Density	[kg/m ³]	Plant specific					
Internal Bond strength EN 319	[N/mm ²]	0.40	0.35	0.30	0.25	0.20	
Bending strength EN 310	[N/mm ²]	11.0	11.0	10.5	9.5	8.5	
Modulus of elasticity EN 310	[N/mm ²]	1,800	1,600	1,500	1,350	1,200	
Surface soundness EN 311	[N/mm ²]	0.8					
Moisture content *1 EN 322	[%]	5-7					
Formaldehyde content *2 EN 120	[mg/100g]	E1 EPF-S					
General Tolerances							
Length and width tolerance EN 324	[mm]	± 5.0					
Squareness EN 324	[mm/m]	≤ 2.0					
Edge straightness tolerance EN 324	[mm/m]	≤ 1.5					
Thickness tolerance EN 324 (sanded boards)	[mm]	± 0.30					
Tolerance on the mean density within a board EN 323	[%]	± 10					
Building physical properties							
Fire behaviour category							
Board thickness > 9 mm and density ≥ 600 kg/m ³ in line with EN13986		D-s2, d0 DFI- s1					
Water vapour diffusion resistance value EN13986							
		μ moist			μ dry		
Mean density 600 kg/m ³		15			50		
Mean density 900 kg/m ³		20			50		
Thermal conductivity EN 13986							
Mean density 600 kg/m ³		0.12					
Mean density 900 kg/m ³	[W/(m*K)]	0.18					
Sound absorption EN 13986							
Frequency range							
250 Hz to 500 Hz		0.10					
1000 Hz to 2000 Hz		0.25					
Biological durability EN 13986							
EN 335		Hazard category 1 (no earth contact, dry 20%/65% relative humidity)					
Air sound insulation EN 13986		R = 13 x lg(mA) + 14 (mA = board surface weight kg/m ²)					
PCP content EN 13986	[ppm]	<5					

*1 On delivery

*2 Formaldehyde content:

2:1 According to the "Regulation on the Prohibition of Chemicals (ChemVerbotsV)" annex to § 1, clause 3 from 14th October, 1993 in connection with the publication of the BGA in the federal health sheet 10/91 (S. 487-489) about "testing method for particleboard", uncoated particleboard must not exceed a perforator limit value EN 120 (photometrical - EN 120) of 8 mg HCHO/100g over-dry board at moisture content of 6,5 %. The flexible half-years mean value is max. 6,5 mg HCHO/100g over-dry board.

2:2 According to the EPF (European Panel Federation) uncoated particleboard with reduced formaldehyde release must not exceed perforator limit value (photometrical - EN 120) of 4 mg HCHO/100g over-dry board at moisture content of 6,5 %.

2:3 According to the California Air Resources Board (CARB) regulation CCR-17-93120.2(a) - Phase 2.

2:4 According to 2:2 and 2:3 the raw particleboard corresponds to the IKEA formaldehyde specification IOS MAT 0003, version AA-10899-9.

2:5 Coated particleboard with reduced formaldehyde release – perforator limit value (photometrical - EN 120) of 5,0 mg/100g over-dry board at moisture content of 6,5 %.

Signed for and on behalf off he manufacturer by:

Manfred Riepertinger
PM Environment & Core Products

St. Johann in Tirol 22.07.2013

Provisional note:

This document has been carefully drawn up to the best of our knowledge. We accept no liability for any mistakes, errors in standards or printing errors. In addition, technical modifications can result from the continuous further development, as well as from changes in standards and documents originating from statutory bodies. The contents of this technical leaflet should therefore not be considered as instructions for use or as legally binding.