

TECHNICAL DATASHEET		
EGGER PRO COMFORT		Classic
Coreboard		HDF swell stopp plus
Profil		The patented UNI fit! installation system stands for a quick and simple installation process without glue. Produced under the licence of Flooring Industries™.
Guarantee domestic area		according to Egger Guarantee
Guarantee comercial area		according to Egger Guarantee
Antistatic properties according EN1815		not available
Class of use	31	
European Norm		
Format	CLASSIC	
Dimension mm (length x width)	1292 x 193	
Complete thickness	10	
Integrated underlay	yes, made from natural cork	
Bevel	WV4	
Pallet	Packaging	
Paket information	One-way-pallet	
	Piece	7
	m2	1,76
		48
	kg	14,22
	Piece	336
	m2	84,48
	kg	702,00
Classification and general requirements according to EN16511:2014		
abrasion resistance according EN13329, Annex E	AC3 (IP ≥ 600)	
impact resistance according EN13329, Annex F	≥ 800 mm	
resistance to staining EN 438 - 2	group 1 + 2: level 4 group 3: level 3	
Thickness swelling according ISO 24336	≤ 20 %	
tolerance of top layer according ISO 24337	length ± 0,5 mm width ± 0,1 mm thickness ± 0,5 mm	
Static indentation by constant pressure according EN24343-1 (EN/ISO)	≤ 0,3	
Effect of a castor chair according EN425	10.000 cycles	
Thermal resistance according to EN 12667	0,09m2 K/W	
Impact Sound Reduction according to EN ISO 10140 -3	≤16 dB	
Room Sound Reduction IHD W 431	43% (1)	

\* reference flooring construction: 7 mm laminate flooring on 3 mm PE-Foam and 0,2 mm PE-Film  
The determined room sound improvement gives the percentage reduction of the loudness feeling relating to the reference.

