






Техническая памятка

Подложки под ламинированные напольные покрытия компании ЭГГЕР

Материал подложки, толщиной от 1,5 до 3,0 мм и рекомендованным напряжением при сжатии CS 60 кПа (6т/м²) или минимум CS 10 кПа (10т/м²), предназначенный для шумоподавления

Звукоизоляционные подложки подходящие под напольные покрытия ЭГГЕР

Производитель или Дистрибьютор	Марка подложки	Толщина mm				
						
EGGER Retail Products	Silenzio Easy	2,0	✓	✓	✓	✓
EGGER Retail Products	Silenzio DUO	1,5	✓	✓	✓	✓
EGGER Retail Products	Silenzio Thermo	5,0	✓	✗	✓	✗
Selit	Selitbloc	1,5	✓	✓	✓	✓
Selit	Ökolit - Kork	2,0	✓	✓	✓	✓
Selit	Selit-Pro Aqua Stop	2,0	✓	✓	✓	✓
Selit	Selitac	2,2	✓	✓	✓	✓
Selit	Selitac	5,0	✓	✗	✓	✗
Selit	Selitac Aqua Stop	5,0	✓	✗	✓	✗
Selit	Axton - laminate combi underlay	2,0	✓	✓	✓	✓
Sekisui Alveo	ALVEO Professional 140	1,5	✓	✓	✓	✓
Sekisui Alveo	ALVEO PRO+ SOUNDPROTECT+ ultra	2,0	✓	✓	✓	✓
Sekisui Alveo	ALVEO Professional Maximum	2,0	✓	✓	✓	✓

Производитель или Дистрибьютор	Марка подложки	Толщина mm				
						
			✓	✓	✓	✓
Ewifoam	Vinclic Professional PU	1,6	✓	✓	✓	✓
Ewifoam	Vinlay Professional SK	2,1	✓	✓	✓	✓
Ewifoam	Duogard Maxima	2,0	✓	✓	✓	✓
Ewifoam	Duogard Maxima Aquastop	2,0	✓	✓	✓	✓
Ewifoam	Silenzia Standard	2,0	✓	✓	✓	✓
Ewifoam	Silenzia Classic	3,0	✓	✗	✓	✗
Ewifoam	Silenzia Classic Aquastop Smart	3,0	✓	✗	✓	✗
Ewifoam	Universol 1000	1,5	✓	✓	✓	✓
Ewifoam	Universol Alu classic	2,6	✓	✓	✓	✓
Ewifoam	Polytex Aquastop Smart	1,6	✓	✗	✗	✗
Ewifoam	Duogard Professional	2,2	✓	✓	✓	✓
Ewifoam	Duogard strong	2,0	✓	✓	✓	✓
PCI Thomsit	Thomsit TF302	2,0	✓	✓	✓	✓
PCI Thomsit	Thomsit TF303	3,0	✓	✓	✓	✓
Arbiton	Secura	3,0	✓	✗	✓	✗
WPT	SRL Solid Viscious Gummimatte	1,7	✓	✓	✓	✓
WPT	Natural Sound Basic SD PU mit Alubeschichtung	2,2	✓	✓	✓	✓
WPT	Natural Sound Comfort SD PU mit Alubeschichtung	3,0	✓	✓	✓	✓
Pregis	LBPE Black + PEE	1,3	✓	✓	✓	✓
Steico	Holzfaserdämmplatte	2,5	✓	✗	✓	✗
Dinamik-Izmir	Dyna Foam	3,0	✓	✓	✓	✓
Stiroleks	Stiroleks XPS	3,0	✓	✓	✓	✓
Ebeco	Ebisol	3,0	✓	✗	✓	✗

Производитель или Дистрибьютор	Марка подложки	Толщина mm	JUST clic! PATENTED EP 1440387; EP 1440387		UNI fit! PATENTED	
Taiga	Soundblocker Foam	3,0	✓	✓	✓	✓
Nostra	Nostrasonic Alu EVA mit ALU PET	3,0	✓	✗	✓	✗
Nostra	Nostrasonic Alu EVA mit ALU PET	2,0	✓	✗	✓	✗
Wallmann	No Noise (Warm, silent and stable)	3,0	✓	✗	✓	✗
Kraiburg Relatec	Damtec® Standard	3,0	✓	✓	✓	✓
Сүдафрика	Whisper LAY - beschichtete Gummimatte	2,0	✓	✓	✓	✓
Parquet Directo	Eva Gold Lamina	2,0	✓	✓	✓	✓
Maxeda (Mac Lean)	Sencys Faltmatte grau	3,0	✓	✓	✓	✓
Maxeda (Mac Lean)	Sencys isotac	5,0	✓	✗	✓	✗
MCD	Indicoustic sol	2,0	✓	✗	✓	✗
MCD	Indicoustic sol PV Plus	3,0	✓	✗	✓	✗
MSD	Indicoustic sol PV Ultra	2,0	✓	✓	✓	✓
Solid	Solid geen	1,0	✓	✓	✓	✓
Solid	Solid pink	1,8	✗	✗	✓	✗
Solid	Solid yellow	2,0	✗	✗	✓	✓
Solid	Solid light green	3,0	✗	✗	✓	✓
Solid	Solid grey	3,0	✗	✗	✓	✗
Solid	Solid violet	5,0	✗	✗	✓	✗



Производитель или Дистрибьютор	Марка подложки	Толщина mm				
Amorin	Rollenkork	2,0	✓	✓	✓	✓
Winoe/ Windmöller	Sound Protect Eco SD	2,0	✓	✓	✓	✓
Repac/ 4 Floor	Acoustic Board	1,8	✓	✓	✓	✓
Repac/ 4 Floor	Acoustic Tech	1,3	✓	✓	✓	✓
Repac/ 4 Floor	Acoustic LVT	1,0	✓	✓	✓	✓
Repac/ 4 Floor	XPS Rolle	2,0	✓	✓	✓	✓
Repac/ 4 Floor	Rollenkork	2,0	✓	✓	✓	✓
Austrotherm	PE 2/200 Schwerschaum	2,2	✓	✓	✓	✓

Данная техническая памятка составлена с особой тщательностью и соответствует сегодняшнему уровню знаний. Сведения, указанные в данной памятке, основаны на опыте и собственных изысканиях и соответствуют тем знаниям, которыми мы располагаем в настоящее время. Они носят информационный характер и не содержат гарантий относительно характеристик продукции или ее пригодности для определенных сфер применения. Мы не несем ответственность за возможные ошибки, опечатки и неточности при указании норм. Кроме того, возможны технические изменения, вытекающие из постоянного совершенствования продукции EGGER Design+ , а также изменений норм и документов публичного права. Поэтому содержание данной технической памятки не является инструкцией по применению.

