

Code Version Release Date SDS\_Eurospan\_en\_US 07 05-23-2022

### **Safety Data Sheet**

#### **EGGER Eurospan**

According to 29 CFR 1910.1200 App D

This product is not hazardous in the form in which it is shipped by the manufacturer, but may become hazardous by wood dust generating downstream activities (e.g. grinding, sanding, cutting or pulverizing).

# Section 1: Identification of the substance/mixture and the company/undertaking

1.1 Product Identifier

Trade name EGGER Eurospan, Eurospan T&G Flooring

Particleboard

Product description Chipboard with reduced Formaldehyde content

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use Decorative use, Furniture, Construction processes

1.3 Details of the supplier of the Safety Data Sheet

Manufacturer/Supplier/Importer Fritz EGGER GmbH & Co. OG (group)
Regional Support Centre EGGER Wood Products LLC(US)

P.O. Box 907

Lexington, NC 27293 T+1-800-940-9633 environment@egger.com

Additional Information e **1.4 Emergency phone number** 

1-800-424-9300/+1703-527-3887 (Chemtrec)

#### Section 2: Hazards identification

#### 2.1 Classification of the substance or mixture

OSHA HCS 2012 This product is generally an article and not hazardous, but is regulated under

OSHA for the release of wood dust during downstream activities, like grinding, sanding, cutting and sawing. The free formaldehyde levels are below OSHA reporting requirements. The classifications below are based upon wood dust:

Skin Irritation 2 Skin Sensitization 1 Eye Mild Irritation 2B Respiratory Sensitization 1

Specific Target Organ Toxicity Repeated Exposure 2: Respiratory Tract Irritation

Carcinogenicity 1A Combustible Dust

#### 2.2 Label elements

Labelling according to paragraph (f) 1910.1200; OSHA29 CFR

Hazard pictograms





Signal word

DANGER

May form combustible dust concentrations in air

SDS\_Eurospan\_en\_US.07

Hazard statements



H315 Causes skin irritation

H317 May cause an allergic skin reaction

H320 Causes eye irritation

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled

H335 May cause respiratory irritation H350 May cause cancer (inhalation)

H373 Causes damage to organs through prolonged or repeated exposure

(inhalation)

Precautionary statements P202 Do not handle until all safety precautions have been read and understood

P210 Keep away from heat/sparks/open flames/hot surfaces - no smoking

P260 Do not breathe dust

P271 Use only outdoors or in a well-ventilated area

P280 Wear protective gloves/protective clothing/eye protection

P302+P352+P305+P351+P338 On contact: Wash thoroughly with water P308+P337+P314+P340+ P264 If exposed or concerned: Get medical

advice/attention if you feel unwell, move to fresh air

#### 2.3 Other hazards

Results of PBT and vPvB assessment

PBT Not applicable vPvB Not applicable

OSHA HCS 2012 This product is not considered hazardous under the U.S. OSHA 29 CFR

1910.1200 Hazard Communication Standard in the form in which it is shipped, but may become hazardous by wood dust generating downstream activities (e.g.

grinding, sanding, cutting or pulverizing).

NFPA Health=1, Flammability=1, Reactivity=0, Special Information=None

HMIS Health=1\*, Flammability=1, Reactivity=0, PFE=E

\*Chronic Health Hazard

E=Safety glasses, gloves, and a dust respirator

### Section 3: Composition/information on ingredients

#### 3.2 Chemical characterization: Mixtures (article)

Description Eurolight composes of a cardboard honeycomb core, glued with polymeric MDI and

wood-based materials as top layers. These wood-based materials consist of wood and

cured amino resins (polymer). See Section 8 for exposure limits discussion.

\*Wood contains trace amounts of various chemicals present in the environment, which are absorbed by trees through natural growth. A comprehensive listing of species is available upon request. The product can contain trace amounts of various chemicals by the use of post-consumer-recycled material.

All products produced at EGGER are certified according to the strict California Air Resources Board (CARB)/ TSCA Title VI. CALIFORNIA RESIDENTS:

WARNING: This product can expose you to chemicals including formaldehyde, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

#### Section 4: First aid measures

### 4.1 Description of first aid measures

General information No special measures required regarding the product in the form it is shipped,

downstream activities like cutting, sawing or grinding can generate dust. To avoid health hazards while these downstream activities, take note of the following

measures:

Inhalation If breathing is difficult, remove victim to fresh air and keep at rest in a position

comfortable for breathing.

Skin Wash with plenty of soap and water. If skin irritation occurs: Get medical

advice/attention. Take off contaminated clothing and wash before reuse. After

contact with the molten product, cool rapidly with cold water

Eye Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/attention.

Ingestion Rinse mouth thoroughly with water. Get medical attention if you feel unwell and

contact a poison control center or medical professional.



#### 4.2 Most important symptoms and effects, both acute and delayed

Refer to Section 11 – Toxicological Information

#### 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available

### Section 5: Firefighting measures

#### 5.1 Extinguishing media

Use firefighting measures that suit the environment Water

Fire-extinguishing powder

Carbon dioxide

Foam

#### 5.2 Special hazards arising from the substance or mixture

EGGER Eurolight is a Class A combustible material. If involved in a fire, product will burn.

EGGER Eurolight is not an explosion hazard. Sawing, sanding, or machining EGGER Eurolight can result in the by-product wood dust. Wood dust may present a strong to severe explosion hazard if a dust cloud contacts an ignition source.

Airborne concentrations of 15 grams per cubic meter are often used as the lower explosive limit (LEL) for wood dusts.

OSHA interprets the explosive level as having no visibility within five feet or less.

In case of fire, the following gases can be released:

Carbon dioxide (CO2), Carbon monoxide (CO), Oxides of Nitrogen and other hazardous gases and particles

#### 5.3 Advice for firefighters

Protective equipment Mouth respiratory protective device

Additional information Prevent formation of dust

Dispose of fire debris and contaminated firefighting water in accordance with official regulations.

#### Section 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal Precautions Do not breathe dust.

Emergency Procedures No emergency procedures are expected to be necessary if material is used

under ordinary conditions as recommended.

#### 6.2 Environment precautions

No special measures required

#### 6.3 Methods and material for containment and cleaning up

Not applicable for product in purchased form. Dust generated from sawing, sanding, drilling or routing this product may be vacuumed or shoveled for recovery or disposal. Wood dust clean-up and disposal activities should be accomplished in a manner to minimize of airborne dust.

Dispose of the material collected according to regulations

#### 6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment

See Section 13 for disposal information

### Section 7: Handling and storage

#### 7.1 Precautions for safe handling

Use good safety and industrial hygiene practices. Minimize dust generation and accumulation. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces. Wear a respiratory mask if using hand tools without a dust extraction device. Observe all liability insurance association regulations for commercial processing operations (e.g. safety goggles).

Information on protection against explosions and fires:

Avoid formation of dust

#### 7.2 Conditions for safe storage, including any incompatibilities

Storage

No special precautions for handling product. Use good safety and industrial hygiene practices. Minimize dust generation and accumulation. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces.

Keep away from ignition sources



#### 7.3 Specific end use(s)

No further relevant information available

### Section 8: Exposure controls/personal protection

#### 8.1 Control parameters

Wood dust needs to be controlled while cutting, sawing, drilling or other dust generating processes are performed.

#### 8.2 Exposure controls

O.Z Exposure cor	1003			
	Result	ACGIH 2007	NIOSH	OSHA
Wood dust	TWAs	1mg/m³ TWA	1mg/m³ TWA	15mg/m³, total
		As Wood dust, all soft	As Wood dust, all soft and	dust(5mg/m³, respirable
		and hard w oods	hard w oods	fraction)
				(as nuisance dust)
Formaldehyde	TWAs	0.3ppm TLV	0.016ppm TWA, 0.1ppm	0.75ppm TWA, 2ppm
(50-00-0)			Ceiling (15 minutes)	STEL, 0.5ppm action
				level

Engineering measures/controls

Personal Protective Equipment Pictograms



Respiratory

Eye/Face Hands Skin/Body

General Industrial Hygiene Considerations

Environmental Exposure Controls

Adequate ventilation systems as needed to control concentrations of airborne contaminants below applicable threshold limit values. Due to the explosive potential of wood dust when suspended in air, precautions should be taken during sanding, sawing or machining of wood products to prevent sparks or other ignition sources in ventilation equipment. Use of totally enclosed motors is recommended.





Use of a NIOSH/MSHA approved dust respirator is recommended where airborne dust levels exceed appropriate PELs and TLVs Wear safety glasses

Wear protective gloves Rubberized cloth, canvas or leather gloves Wear long sleeves and/or protective coveralls.

Practice good housekeeping and avoid creating/breathing dust Do not allow dust to collect. Maintain, clean, and fit test respirators I accordance with OSHA regulations.

No data available

### Section 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

or morriagon on baolo p	The month and on on on one of the original of		
Physical State	solid	Evaporation rate	Not relevant
Color	Yellow to brown	Partitions coefficient	Not relevant
Flammability	D, d0, s2 (EN13986)	Autoignition	536-662°F
Odor	No distinctive odor	Decomposition temperature	No data available
Vapor Pressure	Not relevant	Viscosity	No data available
Odor threshold	Not relevant	Burning time	No data available
Vapor density	No data available	Density	approx. 660kg/m³ (EN 197-1)
рН	Not relevant	Oxidizing properties	No data available
Relative density	Not relevant	Explosive limits	No data available



Melting point	Not relevant	Flash point	Not relevant
Freezing point	Not relevant	Boiling point	Not relevant
Solubility	Not soluble in water		

#### 9.2 Other information

No further relevant information available.

### Section 10: Stability and reactivity

#### 10.1 Reactivity

The product is not reactive under normal conditions of use, storage and transport.

#### 10.2 Chemical stability

Stable under recommended storage conditions

Conditions to be avoided: No decomposition if used according to specifications

#### 10.3 Possibility of hazardous reactions

No dangerous reactions known

#### 10.4 Conditions to avoid

Exposure to water, ignition source, high relative humidity and high temperature

#### 10.5 Incompatible materials

Incompatible Materials: acids (strong), Oxidizers (strong)

#### 10.6 Hazardous decomposition products

Hazardous decomposition may occur thermal and/or thermal oxidative decomposition can produce irritating and toxic fumes and gases.

### **Section 11: Toxicological information**

#### 11.1 Information on toxicological effects

Other Material	Not applicable for product in purchased f	from. Individual component information is provided

below if available

Components

Formaldehyde 50-00-0 Acute Toxicity: Ingestion/Oral-RatLD50 > 200mg/kg; Inhalation-RatLD50

	0.578mg/l/4h
GHS Properties	Classification
Acute toxicity	OSHA HCS 2012 - Acute Toxicity - Data lacking (Oral, dermal, inhalation)
Aspiration hazard	OSHA HCS 2012 - Data lacking
Carcinogenicity	OSHA HCS 2012 Carcinogenicity 1A
Germ Cell Mutagenicity	OSHA HCS 2012 - Data lacking
Skin corrosion/Irritation	OSHA HCS 2012 - Skin Irritation 2
Skin sensitization	OSHA HCS 2012 - Skin Sensitizer1
STOT-RE	OSHA HCS 2012 – Specific target Organ Toxicity Repeated Exposure 2
STOT-SE	OSHA HCS 2012 - Specific target Organ Toxicity Single Exposure 3: respiratory Tract Irritation
Toxicity for Reproduction	OSHA HCS 2012 - Data lacking
Respiratory sensitization	OSHA HCS 2012 – Respiratory Sensitizer 1
Serious eye damage/Irritation	OSHA HCS 2012 - Eye Mild Irritation 2B
Target Organs Route(s) of entry/exposure	Skin/dermal. Lungs, Respiratory System Inhalation, Skin, eye

Medical Conditions Dusts may aggravate asthma or other respiratory disorders.

Aggravated by Exposure

#### **Potential Health Effects**

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs include:

#### Inhalation

Acute(Immediate) May cause respiratory irritation

SDS\_Eurospan\_en\_US.07

#### MORE FROM WOOD.



Chronic (Delayed) Repeated and prolonged exposure may cause cancer. Repeated and prolonged exposure

may cause sensitization of the respiratory system.

Skin

Acute(Immediate) May cause irritation

Chronic(Delayed) Repeated and prolonged exposure may cause sensitization

Eye

Acute (Immediate) May cause irritation Chronic(Delayed) No data available

Ingestion

Acute(Immediate) Under normal conditions of use, no health effects are expected. Under normal conditions of use, no health effects are expected.

Carcinogenic Effects

Carcinogenic Effects Wood dust is listed by NTP known to be a Human Carcinogen (10th Report), IARC

Monographs: Wood dust, group 1 – IARC Group 1: Carcinogenic to humans; sufficient evidence of carcinogenicity. This classification is primarily baes on studies showing an association between occupational exposure to wood dust and adenocarcinoma of the nasal cavities and paranasal sinuses. IARC did not find sufficient evidence of an association between occupational exposure to wood dust and cancers of the hypopharynx, oropharynx,

lymphatic and hematopoietic systems, lungs, stomach, colon or rectum.

	CAS	OSHA	IARC	NTP
Wood dust as Wood dust, all soft	Not Available	Not listed	Group 1 – Carcinogenic	Know n Human
and hard w oods				Carcinogen
Formaldehyde	50-00-0	Specifically Regulated	Group 1 – Carcinogenic	Know n Human
		Carcinogen		Carcinogen

### **Section 12: Ecological information**

#### 12.1 Toxicity

Formaldehyde: EC50 5.8mg/l/48h (Daphnia magna)

Not applicable for particleboard/MDF

#### 12.2 Persistence and degradability

No further relevant information available

#### 12.3 Bioaccumulative potential

Formaldehyde: log POw: 0.35 Not applicable for particleboard/MDF

#### 12.4 Mobility in soil

No further relevant information available

Generally not hazardous for water

#### 12.5 Results of PBT and vPvB assessment

PBT Not applicable Other adverse effects Not applicable

#### 12.6 Other adverse effects

No further relevant information available

### Section 13: Disposal considerations

#### 13.1 Waste treatment methods

Recommendation Disposal according to local regulations

Uncleaned packaging Dispose of packaging according to regulations on the disposal of packaging recommendations

### **Section 14: Transport information**

#### 14.1 UN-number

ADR, ADN, IMDG, IATA Void

14.2 UN proper shipping name

SDS\_Eurospan\_en\_US.07 Page 6 of 8



ADR, ADN, IMDG, IATA Void

14.3 Transport hazard class(es)

ASR, ADN, IMDG, IATA class

14.4 Packing group

ADR, IMDG, IATA Void

#### 14.5 Environmental hazards

Not applicable

#### 14.6 Special precautions for user

Not applicable

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

#### **UN "Model Regulation"**

Void

### **Section 15: Regulatory Information**

## 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

substance or mixture					
NPCA-HMIS® III					
Category	Rating	Description			
Chronic Health Flammability	* 0 1	Chronic (long-term) health effects may result from repeated overexposure (dust)  No significant risk to health  Material that require considerable preheating, under all ambient temperature conditions, before ignition and combustion can occur			
Physical Hazard Personal protection	0	Material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive			
NFPA® 704					
Category	Degree of hazard	Description			
Flammability	1	Material that require conditions, before i			der all ambient temperature cur
Health	0	Material that, under emergency conditions, would offer no hazard beyond that of ordinary combustible material			
Instability Special hazard	0	Material that is normally stable, even under fire conditions			
SARA Hazard Classifications Acute, Chronic					
Inventory Component	CAS		Canada DS	SL	TSCA
EGGER Eurospan Not applicable		Not listed. All components are on the Canada DSL or are excluded from listing or below de minimis reporting		Not listed. All components are on the TSCA inventory or are excluded from listing or below de minimis reporting	
		N/A 50-00-0	Not listed B1, D1A, D2A,	D2B	
EGGER Eurospan and ingredients (unless listed below)		N/A	Not listed		

50-00-0

50-00-0

N/A

U.S.-OSHA - Process Safety Management - Highly hazardous Chemicals

EGGER Eurospan and ingredients (unless listed below) N/A

EGGER Eurospan and ingredients (unless listed below)

Minimis)

Not listed

1000lb TQ

Not listed

SDS\_Eurospan\_en\_US.07

U.S. - CERCLA - Hazardous Substances

Formaldehyde

Formaldehyde

Environment

0.1% (concentration in product is below de

#### MORE FROM WOOD.



Formaldehyde 50-00-0 100lb final RQ U.S. - CERCLA/SARA - Section 304 EHS RQ EGGER Eurospan and ingredients (unless listed below) N/A Not listed Formaldehvde 50-00-0 100lb EPCRARQ U.S. - EPCRA -Section 302 (EHS) TPQ EGGER Eurospan and ingredients (unless listed below) N/A Not listed Formaldehyde 50-00-0 500lb TPQ U.S. - EPCRA - Section 313 - Toxic Chemicals

EGGER Eurospan and ingredients (unless listed below) N/A Not listed

Formaldehyde 50-00-0 0.1% (concentration in product is below de

Minimis)

United States – California

Environment

U.S. – California – Proposition 65 – Carcinogens List

EGGER Eurospan and ingredients (unless listed below) N/A Not listed

Formaldehyde 50-00-0 carcinogen, NSRL 40µg/day

Wood dust as Wood dust, all soft and hard woods N/A carcinogen

**15.2 Chemical Safety Assessment** 

A Chemical Safety Assessment has not been carried out

#### **Section 16: Other information**

This information is based on our present knowledge and comes from sources believed to be accurate or otherwise technically correct. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Initial release 08-27-2017 Last Revision Date 05-23-2022