


# Technical leaflet

## Underlay materials under EGGER Laminate Flooring

Coding: TL Laminat EN  
ID 1827  
Revision: 07  
Approved: 22/02/2019  
Page: 1 of 4

Underpayments for sound reduction with a thickness of 1.5 to 3.0 mm and a recommended compression strength  $CS \geq 60$  kPa, but at least with  $CS \geq 10$  kPa



### Suitable/ approved underlay materials

Producer or Distributor	Underlay material	Thickness in mm				
EGGER Retail Products	Silenzio Easy	2.0	✓	✓	✓	✓
EGGER Retail Products	Silenzio DUO	1.5	✓	✓	✓	✓
EGGER Retail Products	Silenzio Thermo	5.0	✓	✗	✓	✗
Selit	Selitbloc	1.5	✓	✓	✓	✓
Selit	Ökolit - Kork	2.0	✓	✓	✓	✓
Selit	Selit-Pro Aqua Stop	2.0	✓	✓	✓	✓
Selit	Selitac	2.2	✓	✓	✓	✓
Selit	Selitac	5.0	✓	✗	✓	✗
Selit	Selitac Aqua Stop	5.0	✓	✗	✓	✗
Selit	Axton - laminate combi underlay	2.0	✓	✓	✓	✓
Sekisui Alveo	ALVEO Professional 140	1.5	✓	✓	✓	✓
Sekisui Alveo	ALVEO PRO+ SOUNDPROTECT+ ultra	2.0	✓	✓	✓	✓
Sekisui Alveo	ALVEO Professional Maximum	2.0	✓	✓	✓	✓

Producer or Distributor	Underlay material	Thickness in mm				
Ewifoam	Vinclic Professional PU	1.6	✓	✓	✓	✓
Ewifoam	Vinlay Professional SK	2.1	✓	✓	✓	✓
Ewifoam	Duogard Maxima	2.0	✓	✓	✓	✓
Ewifoam	Duogard Maxima Aquastop	2.0	✓	✓	✓	✓
Ewifoam	Silenzia Standard	2.0	✓	✗	✓	✗
Ewifoam	Silenzia Classic	3.0	✓	✗	✓	✗
Ewifoam	Silenzia Classic Aquastop Smart	3.0	✓	✗	✓	✗
Ewifoam	Universol 1000	1.5	✓	✓	✓	✓
Ewifoam	Universol Alu classic	2.6	✓	✓	✓	✓
Ewifoam	Polytex Aquastop Smart	1.6	✓	✗	✗	✗
Ewifoam	Duogard Professional	2.2	✓	✓	✓	✓
Ewifoam	Duogard strong	2.0	✓	✓	✓	✓
PCI Thomsit	Thomsit TF302	2.0	✓	✓	✓	✓
PCI Thomsit	Thomsit TF303	3.0	✓	✓	✓	✓
Arbiton	Secura	3.0	✓	✗	✓	✗
WPT	SRL Solid Viscious Gummimatte	1.7	✓	✓	✓	✓
WPT	Natural Sound Basic SD PU mit Alubeschichtung	2.2	✓	✓	✓	✓
WPT	Natural Sound Comfort SD PU mit Alubeschichtung	3.0	✓	✓	✓	✓
Pregis	LBPE Black + PEE	1.3	✓	✓	✓	✓
Steico	Holzfaserdämmplatte	2.5	✓	✗	✓	✗
Dinamik-Izmir	Dyna Foam	3.0	✓	✓	✓	✓
Stiroleks	Stiroleks XPS	3.0	✓	✓	✓	✓



Producer or Distributor	Underlay material	Thickness in mm	JUST clic!		UNI fit!	
Ebeco	Ebisol	3.0	✓	✗	✓	✗
Taiga	Soundblocker Foam	3.0	✓	✓	✓	✓
Nostra	Nostrasonic Alu EVA mit ALU PET	3.0	✓	✗	✓	✗
Nostra	Nostrasonic Alu EVA mit ALU PET	2.0	✓	✗	✓	✗
Wallmann	No Noise ( Warm, silent and stable)	3.0	✓	✗	✓	✗
Kraiburg Relatec	Damtec® Standard	3.0	✓	✓	✓	✓
South Africa	Whisper LAY - beschichtete Gummimatte	2.0	✓	✓	✓	✓
Parquet Directo	Eva Gold Lamina	2.0	✓	✓	✓	✓
Maxeda (Mac Lean)	Sencys Faltmatte grau	3.0	✓	✓	✓	✓
Maxeda (Mac Lean)	Sencys isotac	5.0	✓	✗	✓	✗
MCD	Indicoustic sol	2.0	✓	✗	✓	✗
MCD	Indicoustic sol PV Plus	3.0	✓	✗	✓	✗
MSD	Indicoustic sol PV Ultra	2.0	✓	✓	✓	✓
Amorin	Rollenkork	2.0	✓	✓	✓	✓
Winoe/ Windmöller	Sound Protect Eco SD	2.0	✓	✓	✓	✓
Repac/ 4 Floor	Acoustic Board	1.8	✓	✓	✓	✓
Repac/ 4 Floor	Acoustic Tech	1.3	✓	✓	✓	✓
Repac/ 4 Floor	Acoustic LVT	1.0	✓	✓	✓	✓
Repac/ 4 Floor	XPS Rolle	2.0	✓	✓	✓	✓
Repac/ 4 Floor	Rollenkork	2.0	✓	✓	✓	✓
Austrotherm	PE 2/200 Schwerschaum	2.2	✓	✓	✓	✓
Repac	XPS Platte grau	3,0	✓	✓	✓	✓



Producer or Distributor	Underlay material	Thickness in mm	JUSTclick! PATENTED <small>EP1442837; EP1442587</small>		UNI fit! PATENTED	
Opti-Step	Sealed Air Opti-Step 3000	1.2	✓	✓	✓	✓

**revisional note:**

This technical data sheet has been carefully drawn up to the best of our knowledge. It is intended for information only and does not constitute a guarantee in terms of product properties or its suitability for specific applications. It is based on practical experiences, our own tests and corresponds to our present state of knowledge. We accept no liability for any mistakes, errors in standards, or printing errors. In addition, technical modifications may result from the continuous development of EGGER flooring, as well as from changes to standards and public law documents. Therefore, the content of these processing instructions cannot serve as instructions for use nor as a legally binding basis.

