

| TECHNICAL DATASHEET   |   |  |
|---|---|--|
| EGGER PRO COMFORT   |   | Classic  |
| Coreboard   |   | HDF swell stopp plus   |
| Profil  |   | The patented UNI fit! installation system stands for a quick and simple installation process without glue. Produced under the licence of Flooring Industries™. |
| Guarantee domestic area   |   | according to Egger Guarantee   |
| Guarantee comercial area  |   | according to Egger Guarantee   |
| Antistatic properties according EN1815                                |   | not available  |
| Class of use  | 32  |  |
| European Norm   |   |  |
| Format  | CLASSIC   |  |
| Dimension mm (length x width)   | 1292 x 193  |  |
| Complete thickness  | 10  |  |
| Integrated underlay   | yes, made from natural cork                             |  |
| Bevel   | WV4   |  |
|   | Packaging   |  |
| Pallet  | One-way-pallet  |  |
| Paket information   |   |  |
|   | Piece   | 7  |
|   | m2  | 1,75   |
|   | kg  | 14,22  |
| Pallet information  |   |  |
|   | Piece   | 336  |
|   | m2  | 83,78  |
|   | kg  | 702,00   |
| Classification and general requirements according to EN16511          |   |  |
| abrasion resistance, test methode A according EN13329, Annex E        | IP ≥ 1200 cycles  |  |
| impact resistance, test methode "big ball" according EN13329, Annex H | ≥ 1200 mm   |  |
| resistance to staining EN 438 - 2                                     | group 1 + 2: level 5<br>group 3: level 4                |  |
| Thickness swelling according ISO 24336                                | ≤ 18 %  |  |
| tolerance of top layer according ISO 24337                            | length ± 0,5 mm<br>width ± 0,1 mm<br>thickness ± 0,5 mm |  |
| Static indentation by constant pressure according EN24343-1 (EN/ISO)  | ≤ 0,2 mm  |  |
| Effect of a castor chair according EN425                              | 25.000 cycles   |  |
| Thermal resistance according to EN 12667                              | 0,09 m2 K/W   |  |
| Impact Sound Reduction according to EN ISO 10140 -3                   | ≤16 dB  |  |
| Room Sound Reduction IHD W 431  | ≤ 43% (1)   |  |
| micro scratch resistance EN16094                                      | ≤ MSR-A3e   |  |

\* reference flooring construction: 7 mm laminate flooring on 3 mm PE-Foam and 0,2 mm PE-Film  
The determined room sound improvement gives the percentage reduction of the loudness feeling relating to the reference.



**TECHNICAL DATASHEET**

|   |   |  |
|---|---|--|
| EGGER PRO COMFORT   |   | Large  |
| Coreboard   |   | HDF swell stopp plus   |
| Profil  |   | The patented UNI fit! installation system stands for a quick and simple installation process without glue. Produced under the licence of Flooring Industries™. |
| Guarantee domestic area   |   | according to Egger Guarantee   |
| Guarantee comercial area  |   | according to Egger Guarantee   |
| Antistatic properties according EN1815                                |   | not available  |
| Class of use  | 32  |  |
| European Norm   |   |  |
| Format  | Large   |  |
| Dimension mm (length x width)   | 1292 x 245  |  |
| Complete thickness  | 10  |  |
| Integrated underlay   | yes, made from natural cork                             |  |
| Bevel   | WV4   |  |
| <b>Packaging</b>  |   |  |
| Pallet  | One-way-pallet  |  |
| <b>Paket information</b>  |   |  |
|   | Piece   | 7  |
|   | m2  | 2,22   |
|   | kg  | 18,09  |
| <b>Pallet information</b>   |   |  |
|   | Piece   | 273  |
|   | m2  | 86,42  |
|   | kg  | 725,00   |
| <b>Classification and general requirements according to EN16511</b>   |   |  |
| abrasion resistance, test methode A according EN13329, Annex E        | IP ≥ 1200 cycles  |  |
| impact resistance, test methode "big ball" according EN13329, Annex H | ≥ 1200 mm   |  |
| resistance to staining EN 438 - 2                                     | group 1 + 2: level 5<br>group 3: level 4                |  |
| Thickness swelling according ISO 24336                                | ≤ 18 %  |  |
| tolerance of top layer according ISO 24337                            | length ± 0,5 mm<br>width ± 0,1 mm<br>thickness ± 0,5 mm |  |
| Static indentation by constant pressure according EN24343-1 (EN/ISO)  | ≤ 0,2 mm  |  |
| Effect of a castor chair according EN425                              | 25.000 cycles   |  |
| Thermal resistance according to EN 12667                              | 0,09 m2 K/W   |  |
| Impact Sound Reduction according to EN ISO 10140 -3                   | ≤ 16 dB   |  |
| Room Sound Reduction IHD W 431  | ≤ 43% (1)   |  |
| micro scratch resistance EN16094                                      | ≤ MSR-A3e   |  |

\* reference flooring construction: 7 mm laminate flooring on 3 mm PE-Foam and 0.2 mm PE-Film  
The determined room sound improvement gives the percentage reduction of the loudness feeling relating to the reference.



| TECHNICAL DATASHEET   |       |  |
|---|-------|--|
| EGGER PRO COMFORT   |       | Kingsize   |
| Coreboard   | E1    | HDF swell stopp plus   |
| Profil  |       | The patented UNI fit! installation system stands for a quick and simple installation process without glue. Produced under the licence of Flooring Industries™. |
| Guarantee domestic area   |       | according to Egger Guarantee   |
| Guarantee comercial area  |       | according to Egger Guarantee   |
| Antistatic properties according EN1815                                |       | not available  |
| Class of use  |       | 32   |
| European Norm   |       |  |
| Format  |       | Kingsize   |
| Dimension mm (length x width)   |       | 1292 x 327   |
| Complete thickness  |       | 10   |
| Integrated underlay   |       | yes, made from natural cork  |
| Bevel   |       | WV4  |
|   |       | Packaging  |
| Pallet  |       | One-way-pallet   |
| Paket information   |       |  |
|   | Piece | 5  |
|   | m2    | 2,11   |
|   | kg    | 17,49  |
| Pallet information  |       |  |
|   | Piece | 200  |
|   | m2    | 84,50  |
|   | kg    | 750  |
| Classification and general requirements according to EN16511          |       |  |
| abrasion resistance, test methode A according EN13329, Annex E        |       | IP ≥ 1200 cycles   |
| impact resistance, test methode "big ball" according EN13329, Annex H |       | ≥ 1200 mm  |
| resistance to staining EN 438 - 2                                     |       | group 1 + 2: level 5<br>group 3: level 4   |
| Thickness swelling according ISO 24336                                |       | ≤ 18 %   |
| tolerance of top layer according ISO 24337                            |       | length ± 0,5 mm<br>width ± 0,1 mm<br>thickness ± 0,5 mm  |
| Static indentation by constant pressure according EN24343-1 (EN/ISO)  |       | ≤ 0,2 mm   |
| Effect of a castor chair according EN425                              |       | 25.000 cycles  |
| Thermal resistance according to EN 12667                              |       | 0,09 m2 K/W  |
| Impact Sound Reduction according to EN ISO 10140 -3                   |       | ≤ 16 dB  |
| Room Sound Reduction IHD W 431  |       | ≤ 43% (1)  |
| micro scratch resistance EN16094                                      |       | ≤ MSR-A3e  |

\* reference flooring construction: 7 mm laminate flooring on 3 mm PE-Foam and 0,2 mm PE-Film  
The determined room sound improvement gives the percentage reduction of the loudness feeling relating to the reference.

