

TECHNICAL DATASHEET		
EGGER PRO LAMINATE FLOORING		8/32 Classic
Coreboard	E1 HCHO	HDF swell stopp plus
Profile	JUST clic! Patented	The patented EGGER installation system JUST clic! stands for quick and simple installation process without glue. Patented as JUST clic! EP 1 441 087 and EP 1 462 587
Guarantee domestic area	20	according to Egger Guarantee
Guarantee comercial area	5	according to Egger Guarantee
Antistatic properties according EN1815	Antistatic	yes, < 2 kV
Class of use	32	
European Norm EN13329	EN 13329-32	
Format	CLASSIC	
Dimension mm (length x width)	1292 x 192	
Complete thickness	8	
Thickness of silenzio@ special cellulose		
Bevel	-	
Pallet	Packaging One-way-pallet	
Paket information		
	Piece	8
	m2	1,98
	kg	14,46
Pallet information		
	Piece	480
	m2	119,07
	kg	877,00
Classification and general requirements according EN13329		
Abrasion resistance according EN13329, annex E	AC4 (IP ≥ 4000)	
Impact resistance according EN13329, annex H	Big ball: ≥ 750 mm Small ball: ≥ 12 N	
Resistance to staining EN438	Group 1 + 2: level 5 group 3: level 4	
Effect of furniture leg according EN424	No damage shall be visible, when tested with foot Type 0 artefact	
Effect of a castor chair according EN425 (Type W)	No change in appearance or damage	
Thickness swelling according ISO 24336	≤ 18 %	
Tolerance of top layer according EN13329	length ± 0,5 mm width ± 0,1 mm thickness ± 0,5 mm	
Light fastness according EN13329	grey scale ≥ level 4 (EN:20105-A02)	
Static indentation by constant pressure according EN ISO 24343-1	< 0,05	
Surface soundness according EN13329, annex D	≥ 1,25 N/mm2	
Thermal resistance according to EN 12667	0,07 m² K/W	

