

# TECHNICAL LEAFLET

## EGGER Premium Tape



### Tradename

EGGER Premium Tape

### Description

EGGER Premium Tape is a medium performance, strong, polyethylene coated waterproof cloth tape, coated with a pressure sensitive adhesive. The standard colour is white but it is also available in other colours including black, silver, grey, red, yellow, blue, green and brown.

### Applications

- Sealing the joints between boards in particleboard T&G flooring
- Duct sealing – covering joints in hot air and insulating materials
- Fixing and holding of wires and cables, especially on film sets
- Heavy duty and export packaging for drum sealing and colour coding
- Double glazing and unit sealing
- Masking applications
- Carpet joining and edging
- Colour coding and identification
- Holding and fixing of cables and wires
- Joining and splicing applications
- Ideal for general purpose applications where added strength and performance are required

### Benefits

- Excellent waterproof properties
- Good strength
- Highly flexible and conformable
- Good initial tack and ultimate adhesion
- Good unwind
- Easy tear
- Peels off easily after use
- Excellent low and high temperature performance - service temperature 0 to 100°C

### Technical properties

| Property            | Unit | Nominal value | Test method |
|---------------------|------|---------------|-------------|
| Tensile strength    | N/cm | 48            | IEC 454-2   |
| Adhesion to steel   | N/cm | 4             | IEC 454-2   |
| Adhesion to backing | N/cm | 2.5           | IEC 454-2   |

### Standard details

Thickness [mm]: 0.3  
Roll length [m]: 25, 50  
Roll width [mm]: 38, 50, 75 and 100  
Core: Cardboard  
Packaging: Bulk packed using interleaving sheets between layers

NOTE: Information on stock items, non standard sizes and lead times is available on request

The information contained within this leaflet is based on practical experience and reflects our current state of knowledge. It is intended for information only and does not constitute a guarantee in terms of product properties or their suitability for specific applications. Unless otherwise stated, our General Terms and Conditions apply.