

## Adhesive recommendation



EGGER Design-Floor GreenTec

Subsurface	Any moisture must be prevent from the subfloor with appropriate waterproofing					
	Calcium sulphate screed CA Calcium sulphate screed CAF	Cement screed CT	Mastic asphalt screed AS	Concrete Underground	Chipboard / OSB Board / Installation Board	Dry screed
Residual moisture	unheated < 0,5 CM % heated < 0,3 CM %	< 2,0 CM % < 1,8 CM %	Not applicable	< 6,0 Gew.-%	Follow manufacturer's instructions	
Substrate preparation	grind and vacuum thoroughly BEB- u. TKB Follow the information sheets "Assessment and preparation of substrates"			Shot blasting Vacuuming	grind and vacuum thoroughly	
Primer	GRIP A500 MULTI 1:1 water-diluted GRIP A766 ECO+ 1:1 water-diluted	GRIP A500 MULTI 1:1 water-diluted GRIP A766 ECO+ 1:1 water-diluted	GRIP A936 XPRESS Use only in the absence of sanding	HYTEC E730 XTREM Apply twice time with sanding	GRIP A500 MULTI 1:1 water-diluted GRIP A766 ECO+ 1:1 water-diluted	GRIP A500 MULTI 1:1 water-diluted GRIP A766 ECO+ 1:1 water-diluted
Levelling compound	SL G720 ALPHA BEST SL C710 BEST Thickness min. 2mm	SL G720 ALPHA BEST SL C710 BEST Thickness min. 2mm	SL G720 ALPHA BEST SL C710 BEST Thickness min. 2mm max. 5 mm	SL G720 ALPHA BEST SL C710 BEST Thickness min. 2mm	SL G720 ALPHA BEST SL C710 BEST Thickness min. 2mm	SL G720 ALPHA BEST SL C710 BEST Thickness min. 2mm
	<b>ADD BOSTIK GLASS Fibres</b>					

Coating /Article / Collection	Adhesive	Basis	Trowel toothing	Ecode	Specials
EGGER Design-Floor GreenTec	WOOD H550 ECO PLUS Stix A550 Power Elastic	Stix A550 Power Elastic – Dispersion	Stix A550 Power Elastic Tooth profile B2	EC1+ / Blue Angel	For application in areas of direct sunlight, such as conservatories, the adhesive STIX H995 ELASTIC XTREM must be used.

All the adhesives listed are tested in accordance with „Community of Emission Controlled Installation Materials“ and classified accordingly as „EC1“ or „EC1+“. Furthermore, some products are certified with the „Blue Angel“ according to ZU 113. For further questions, please contact the construction engineering department of Bostik.

Please observe the technical data sheets of the above mentioned products as well as the installation instructions of the flooring manufacturer. These Adhesive recommendations are subject to the technical rules of the VOB, DIN 18356 „Parquet and wood paving work“ and VOB, DIN 18365 „Floor covering work“.

