



	EGGER Design Flooring GreenTec with LUGATO	
Adhesive	DESIGNBELAGSKLEBSTOFF DOPPEL PLUS (moisture-resistant, also suitable for wall areas – strong)	
Serrated trowel	TKB A2, TKB B1, TKB B2	
Drying time	Flash-off time: 10 - 20 minutes Laying time: 20 - 30 minutes Curing time: 24 - 48 hours	
Floor levelling compound (if required)	GLÄTT- & FEINSPACHELMASSE (living area) FLIESST & FERTIG EXTRA (living and wet room area) NEU AUF ALT! (With timber floor boards and chipboard / OSB floors)	
Wall surface levelling (if required)	ROHBAUSPACHEL INNEN (living area) ROHBAUSPACHEL AUSSEN (living and wet room area)	
Sealing beneath designer coverings (if required)	ABDICHTUNGSBAHN (DICHTUNGSBAND, DICHTMANSCHETTE, INNEN- and AUSSENECKE)	
Priming	Do not prime before using DESIGNBELAGSKLEBSTOFF DOPPEL PLUS! Pay attention to the priming instructions for the building materials before using floor / wall fillers!	
The general usage and processing instructions for the mentioned LUGATO products in the respective technical leaflet must be observed.		

	EGGER Design Flooring GreenTec with LUGATO	
Adhesive	PARKETTKLEBSTOFF (in dry living areas)	
Serrated trowel	TKB B2, TKB B3	
Drying time	Flash-off time: 5 - 10 minutes Laying time: 20 - 40 minutes Can be walked on after: >12 hours Load-bearing >24 hours	
Floor levelling compound (if required)	GLÄTT- & FEINSPACHELMASSE (living area) NEU AUF ALT! (With timber floor boards and chipboard / OSB floors)	
Wall surface levelling (if required)	ROHBAUSPACHEL INNEN or -AUSSEN (living area)	
Priming	Do not prime before using PARKETTKLEBSTOFF! Pay attention to the priming instructions for the building materials before using floor / wall fillers!	
The general usage and processing instructions for the mentioned LUGATO products in the respective technical leaflet must be observed.		