

TECHNICAL DATASHEET

EGGER STRIP-EX

PRODUCT:

- EGGER STRIP-EX sealing glue is a high-quality, usable glue especially developed for the groove and tongue sealing of EGGER laminate flooring and flooring with Cork+ technologie flooring.
- The Sealing glue arise a resistance to water concerning DIN EN 204, stress group D3.
- The glue joint is viscous elastic and dries clear.



INSTRUCTIONS FOR USE:

- Laying conditions: temperature: $\leq 18^{\circ}\text{C}$, humidity: 40-70%
- By EGGER flooring with JUST clic profile apply the sealing glue on the top of the tongue on the short and long edge. The glue should ooze out along the complete long and short edge after the panels have been connected together.
- By EGGER flooring with PRO clic profile apply the sealing glue to the long side of the tongue of the new panel to be laid and into the front edge of the groove of the already laid element so that it oozes out on the top along the entire seams when the panels are joined.
- Excess sealing glue is easy to remove from the surface immediately or after a short drying period. Open bottles use as soon as possible.
- Attention: Please take a look into the suitable installation instructions.

TECHNICAL DATAS:

- | | |
|---|---|
| • Content of solids: | 50 + 5 % |
| • Viscosity: | 5.300 \pm 250 mPa.s (Brookfield HAT, @20°C) |
| • MFT (minimum film forming temperature): | ca. 5°C |



PACKAGING:

- Bottle 550 ml
- Usage 550 ml for 20-25 m²

STORAGE:

- Storable in unopened packing minimum 24 months.
- Frostfree and cool between +5 and +25 °C.
- Keep secure out of reach for children.

TRANSPORTCLASSIFICATION:

- Non dangerous goods.