

# Environmental & Health Data Sheet

Self-declaration according to ISO 14021



## EGGER MDF E1E05 TSCA ST CE

The MDF E1E05 TSCA ST CE medium density fibre board is a board-shaped wood based material with reduced formaldehyde content. Due to its homogeneous structure, the EGGER MDF board can be milled three-dimensionally and then painted or faced with a laminate or foil. It is predominantly used coated and as furniture board.

## Raw Materials & Primary Products

### Wood origin

Our plants are certified according to the standard ISO 38200:2018, all paper can be referred to the ISO 38200: 2018 statements. On request and in agreement with your contact person at the EGGER sales department, our products can be declared on our sales documents also with other certification claims, depending on the availability at the production site. Please inquire availability details from your sales contact.

For certificates and an up-to-date list of the regional origin and wood species used in the product, see document available for download at [www.egger.com/environment](http://www.egger.com/environment):

- Manufacturer's Declaration – Timber origins (Pdf)
- Certificate ISO 38200:2018 (Pdf)
- Further 3<sup>rd</sup> party certificates of sustainable wood procurement (Pdf)

### Renewable content

|                      | Renewable content | Fossil-based content |
|----------------------|-------------------|----------------------|
| MDF E1E05 TSCA ST CE | 87 %              | 13 %                 |

Average renewable resource content by dry weight, in relation to all constituent materials (incl. wood, glue and others). Figures may vary between thicknesses.

### Recycled content

|                      | Virgin material | Co-products | Preconsumer recycling material | Postconsumer recycling material |
|----------------------|-----------------|-------------|--------------------------------|---------------------------------|
| MDF E1E05 TSCA ST CE | 34 %            | 66 %        | 0 %                            | 0 %                             |

Average recycling content by dry weight, in relation to all constituent materials (incl. wood, glue and others). Figures may vary between thicknesses.

### Carbon Footprint

|                                      | Global warming potential            |
|--------------------------------------|-------------------------------------|
| 1m <sup>3</sup> MDF E1E05 TSCA ST CE | -669 kg CO <sub>2</sub> -equivalent |

A negative amount indicates that carbon is stored in the product. Data on carbon storage in products (carbon footprint) is taken from the Life Cycle Assessment (LCA) in the Environmental Product Declaration (EPD). GWP 100 (global warming potential over 100 years), cradle-to-gate.

### Constituent materials

| Responsible          | Editor         | Valid until | Revision | Classification | Page    |
|----------------------|----------------|-------------|----------|----------------|---------|
| Riepertinger Manfred | Bender Martina | 16.02.2022  | 1        | Public         | 1 of 10 |

EGGER MDF E1E05 TSCA ST CE is a composite wood based, UMF- and UF-bonded panel. The table below contains 99.9% of the primary products, measured by weight. Proportions may vary between individual product thicknesses. Listed is the average across all thicknesses in one production year. All chemicals have been evaluated and are disclosed down to 1000 ppm.

| Proportion |   | Function               | Composition/ Add. info  |
|------------|---|------------------------|---|
| 87         | % | Dry wood fibres        | Industrial round wood and saw mill by-products  |
| 11         | % | Glue                   | Mix of Urea-Melamine-Formaldehyde Glue (UMF) and Urea-Formaldehyde Glue (UF)<br><i>during the pressing process, the aminoplastic adhesive hardens fully. Under normal conditions, it is bound to the wood and chemically stable</i> |
| <1         | % | Formaldehyde scavenger | Technical Urea  |
| <0.5       | % | Hydrophobing agent     | Paraffine wax emulsion  |

## Manufacturing

### Production plants & their certifications

The product is manufactured at the following locations. For address and certification details, kindly see footnotes at the end of this document.

| Plant <sup>i</sup> | Certifications obtained by this plant |             |           |             |
|--------------------|---------------------------------------|-------------|-----------|-------------|
|                    | Quality                               | Environment | Energy    | Wood origin |
| Gagarin, RU        | ISO 9001                              | –           |           | ISO 32800   |
| Brilon, D          | ISO 9001                              | ISO 14001   | ISO 50001 | ISO 32800   |

## Processing

### Safety

This product is not hazardous in the form in which it is shipped by the manufacturer. Downstream activities (e.g. grinding, sanding, cutting or pulverizing) may generate wood dust, which is hazardous. Wear a respiratory mask if using hand tools without a dust extraction device. Observe all liability insurance association regulations for commercial processing operations (e.g. safety goggles).

### Technical data

See document available for download at [www.egger.com](http://www.egger.com)

- Technical Data Sheet MDF E1E05 TSCA ST (Pdf)

## Use

### Product certification

On request the products can be labelled with a certification<sup>ii</sup> claim according to:

- ISO 38200:2018
- Further 3<sup>rd</sup> party certificates of sustainable wood procurement

To download certificates, see EGGER environmental downloads at [www.egger.com/environment](http://www.egger.com/environment)

## Product emissions & Health aspects

Natural wood constituents may be released in small quantities. Minor amounts of formaldehyde can be detected. During the MDF E1E05 TSCA ST CE's manufacturing processes, heat and pressure is applied in a short cycle press. All resins cure completely into a solid material. In the use phase, the product is chemically stable under normal conditions. There are no known health hazards or health effects to be expected under normal conditions, when the product is used as intended.

| Substance / indicator | Product has been tested and fulfils emission requirement | Requirement          | Requirement details <sup>iii</sup>   |
|-----------------------|--|----------------------|--|
| Formaldehyde          | ✓  | E1                   | Formaldehyde class E1, according to EN 13986+A1:2015-04                    |
| Formaldehyde          | ✓  | E1 (Germany) ≙ E1E05 | German ChemVerbotsVO Formaldehyde class E1 from 1.1.2020, external testing |
| Formaldehyde          | ✓  | CARB P2              | California's Composite Wood Products Regulation California's               |
| Formaldehyde          | ✓  | TSCA                 | U.S. Toxic Substances Control Act, external testing (core board)           |

## End of life – Waste treatment

### Reuse

During remodeling or at the end of the utilization phase of a building, the product can easily be separated and used again for the same applications, if selective deconstruction is practiced. This is only possible if the product has not been bonded over its entire surface.

### Recycling – Material use

The use of post-consumer MDF as a raw material for the production of new MDF boards on large scale is technical not feasible, yet. MDF core boards can be tolerated in small quantities in the waste wood stream, but cannot be used as the sole source for the production of new chipboards.

### Incineration – Energetic use

After its utilization phase, the product should be separated and routed to an energetic recovery, due to its high calorific value of approx. **18.5 MJ/kg**. Upon incineration, kindly observe all locally applicable legal requirements for the correct dimensions, required filter technologies, operating conditions, and legal permissions for burning wood-based panels/ fibreboards.

Waste code according to European Waste Catalogue, depending on origin of the waste:

- 17 02 01 Construction & Demolition Waste Wood or
- 03 01 05 sawdust, shavings, cuttings, wood, particle board and veneer not containing hazardous substances

The product is not classified as hazardous waste. Used MDF E1E05 TSCA ST CE boards can be classified as glued waste wood without halogenated compounds and without wood preservatives.

See also document available for download at [www.egger.com/environment](http://www.egger.com/environment):

- Manufacturer's Declaration – Wood preservatives (Pdf)
- Manufacturer's Declaration – Halogenated organic compounds (Pdf)

## Environmental life cycle assessment

The product has a verified Environmental Product Declaration (EPD) according to ISO 14025 and EN 15804.

- Environmental Product Declaration (EPD) MDF raw boards (Pdf) available for download at [www.egger.com/environment](http://www.egger.com/environment) ]



## Compliance with LEED v4

EGGER MDF E1E05 TSCA ST CE is compliant with the prerequisites for use in LEED certified buildings outside the U.S. Beyond that the usage of EGGER MDF E1E05 TSCA ST CE contributes to gather additional points within the LEED scoring system. The following table shows all LEED credits which are applicable to the usage of our product. As the actually achievable number of points depends on the attributes of all used materials in the LEED building project and further actions by the constructor, we cannot guarantee to obtain the maximum score. For full requirement terms see LEED credit library at [www.usbc.org](http://www.usbc.org).

### Projects outside U.S.

| LEED v4 Requirements for Building Design + Construction (BD+C)<br>New Construction, Core and Shell, Schools, Retail, Healthcare, Data Centers, Hospitality, Warehouses and Distribution Centers                         |  |                | Product contributions   |
|---|--|----------------|---|
| LEED v4 Requirements for Interior Design + Construction (ID+C)<br>Commercial Interiors, Retail, Hospitality   |  |                |   |
| Chapter   | Requirement summary  | Maximum Points |   |
| Material and Resources  | Building Product Disclosure and Optimization - Environmental Product Declarations<br><br>Option 1. Environmental Product Declaration (EPD)   | 1 Point        | This product has a verified Environmental Product Declaration (EPD) according to ISO 14025 and EN 15804. See <ul style="list-style-type: none"> <li>Environmental Product Declaration (EPD) MDF raw boards (Pdf)</li> </ul> available for download at <a href="http://www.egger.com/environment">www.egger.com/environment</a>                          |
|   | Building Product Disclosure and Optimization - Sourcing of Raw Materials<br><br>Option 1.:Raw material source and extraction reporting Third-party verified corporate sustainability reports (CSR) according to an accepted framework.       | 2 Point        | An annual Sustainability report is published in accordance with the GRI standards: "Core" option, and is audited by an independent party. See <ul style="list-style-type: none"> <li>Sustainability report (Pdf)</li> </ul> available for download at <a href="http://www.egger.com/environment">www.egger.com/environment</a> .                        |
| Building Product Disclosure and Optimization - Sourcing of Raw Materials<br><br>Option 2.3: Wood products must be certified by the Forest Stewardship Council or USGBC-approved equivalent.                             | The products is verified by the ISO 38200 : 2018 statements. Additionally, the product can be purchased in other certified qualities on request. Use delivery receipt as evidence document. See also chapter "Wood origin" of this document. |                |   |
| Building Product Disclosure and Optimization - Sourcing of Raw Materials<br><br>Option 2.5: Recycled content is the sum of postconsumer recycled content plus one-half the preconsumer recycled content, based on cost. | Recycled content of the product (based on weight) = 0% + 66%/2 =33 % . See "Constituent materials" section above to obtain further information.  |                |   |
| Material and Resources  | Building Product Disclosure and Optimization - Material Ingredients<br><br>Option 1: Declare.  | 1 Point        | The manufacturer has screened the product to at least 1,000 ppm and has provided a publicly available inventory. See "Constituent materials" section above to obtain further information.   |
| Indor Environmental Quality   | Low-emitting Materials- Formaldehyde emissions evaluation<br><br>For projects <b>outside the U.S.</b> , composite wood must be documented not to exceed a concentration limit of 0.05 ppm of formaldehyde.                                   |                | Product is tested per EN 717-1:2014 for formaldehyde emissions and complies with emissions class E1. See "Product emissions & Health aspects" section above for further information. Please get in touch with your EGGER sales contact or distributor, who are happy to forward the inquiry to get MDF E1E05 TSCA ST CE Formaldehyde test report (Pdf). |

Projects inside U.S.

Please note that formaldehyde emission requirements in LEED v4 are deviating for projects **inside the U.S.** *Requirements given in italics are currently not met by the product.*

| LEED v4 Requirements for Building Design + Construction (BD+C)<br>New Construction, Core and Shell, Schools, Retail, Healthcare, Data Centers, Hospitality, Warehouses and Distribution Centers                         |  |                | Product contributions  |
|---|--|----------------|--|
| LEED v4 Requirements for Interior Design + Construction (ID+C)<br>Commercial Interiors, Retail, Hospitality   |  |                |  |
| Chapter   | Requirement summary  | Maximum Points |  |
| Material and Resources  | Building Product Disclosure and Optimization - Environmental Product Declarations<br><br>Option 1. Environmental Product Declaration (EPD)   | 1 Point        | This product has a verified Environmental Product Declaration (EPD) according to ISO 14025 and EN 15804. See <ul style="list-style-type: none"> <li>Environmental Product Declaration (EPD) MDF raw boards (Pdf)</li> </ul> available for download at <a href="http://www.egger.com/environment">www.egger.com/environment</a> |
|   | Building Product Disclosure and Optimization - Sourcing of Raw Materials<br><br>Option 2.3: Wood products must be certified by the Forest Stewardship Council or USGBC-approved equivalent.  | 1 Point        | The products is verified by the ISO 38200 : 2018 statements. Additionally, the product can be purchased in other certified qualities on request. Use delivery receipt as evidence document. See also chapter "Wood origin" of this document.   |
| Building Product Disclosure and Optimization - Sourcing of Raw Materials<br><br>Option 2.5: Recycled content is the sum of postconsumer recycled content plus one-half the preconsumer recycled content, based on cost. | Recycled content of the product (based on weight) = 0% + 66%/2 = 33 % . See "Constituent materials" section above to obtain further information.   |                |  |
| Material and Resources  | Building Product Disclosure and Optimization - Material Ingredients<br><br>Option 1: Declare.  | 1 Point        | The manufacturer has screened the product to at least 1,000 ppm and has provided a publicly available inventory. See "Constituent materials" section above to obtain further information.  |
| Indor Environmental Quality   | Low-emitting Materials- Formaldehyde emissions evaluation:<br><br>Composite wood must be documented to have low formaldehyde emissions that meet the requirements for ultra-low-emitting formaldehyde (ULEF) resins or no added formaldehyde resins. | 3 Points       | <i>The product does not fulfil ULEF requirements. Glue on a formaldehyde base is used as a binding agent.</i>  |

## Compliance with WELL Building Standard v2™

EGGER MDF E1E05 TSCA ST CE is compliant with the preconditions for use in WELL v2™ certified buildings. Beyond that the usage of this product may contribute to gather additional points within the WELL scoring system. The following table shows all WELL features which are applicable to the usage of our product. *Requirements given in italics are currently not met by the product.* As the actually achievable number of points depends on the attributes of all used materials in the WELL building project and further actions by the constructor, we cannot guarantee to obtain the maximum score. For full requirement terms see WELL feature library at [www.wellcertified.com](http://www.wellcertified.com).

| Requirements                       |   |                | Product contributions   |
|------------------------------------|---|----------------|---|
| Chapter                            | Requirement summary   | Maximum Points |   |
| X01 Material Precautions           | Restrict asbestos, mercury and lead.  | Precondition   | The product complies with this precautions. See Manufacturer's Declaration – Asbestos (Pdf) available for download at <a href="http://www.egger.com/environment">www.egger.com/environment</a> . Please get in touch with the EGGER product sustainability & compliance team at <a href="mailto:environment@egger.com">environment@egger.com</a> to get further declarations concerning the non-use of mercury and lead . |
| X05 Enhanced Material Restrictions | <b>Part 2a Select Compliant Architectural and Interior Products:</b> Flooring products, ceiling and wall panels contain halogenated flame retardants (HFR) at less than 100 ppm.  | 1 Point        | The product complies with this requirement. No halogenated flame retardants (HFR) are used in this product. See "Constituent materials" section above for your documentation. Please get in touch with the EGGER product sustainability & compliance team at <a href="mailto:environment@egger.com">environment@egger.com</a> to get Manufacturer's declaration on the use of halogenated compounds (Pdf).                |
| X05 Enhanced Material Restrictions | <b>Part 2a Select Compliant Architectural and Interior Products:</b> Newly installed floorings and furniture contain Orthophthalates at less than 100 ppm.  |                | In general, no softening agents are used in the production of fibre boards, in particular no phthalates. See "Constituent materials" section above for your documentation   |
| X06 Volatile Compound reduction    | <b>Part 2a Restrict VOC Emissions from Furniture, Architectural and Interior Products:</b> Furniture and wall panels tested per AgBB or CDPH method and VOC emission threshold established.   | 2 Points       | <i>Product is not tested according German AgBB scheme. Use laminated material e.g. EGGER Eurodekor E1E05 TSCA P2 CE to meet this requirement.</i>   |
| X06 Volatile Compound reduction    | <b>Part 2c2 Restrict VOC Emissions from Furniture, Architectural and Interior Products:</b> Composite wood panels meet the formaldehyde standards European E1, TSCA, F*** or LEED v4.1  |                | Product is tested per EN 717-1:2014 for formaldehyde emissions and complies with emissions class E1. See "Product emissions & Health aspects" section above for further information. Please get in touch with your EGGER sales contact or distributor, who are happy to forward the inquiry to get MDF E1E05 TSCA ST CE Formaldehyde test report (Pdf).   |
| X07 Material Transparency          | <b>Part 1: Select Products with Disclosed Ingredients:</b> Promote ingredient disclosure with ingredients identified and disclosed to 1,000 ppm.  | 1 Point        | The product is screened to at least 1,000 ppm and the manufacturer has provided a publicly available inventory within this document. See "Constituent materials" section above for your documentation.  |
| X08 Materials Optimization         | <b>Part 1 Select Material with Enhanced Chemical Restrictions:</b> Newly installed furnishings, built-in furniture, interior finishes and finish materials comply with some combination of the listed programs (e.g. Living Building Challenge Red List Free) | 2 Points       | <i>Currently our product does not participate in any of the listed programs. It does not contribute to achieve points for this requirement.</i>   |
| X08 Materials Optimization         | <b>Part 2 Select Optimized Products:</b> Product is certified by one of the listed programs (e.g. Cradle to Cradle)   |                | <i>Currently our product does not participate in any of the listed programs. It does not contribute to achieve points for this requirement.</i>   |

## Compliance with BREEAM International New Construction 2016

EGGER MDF E1E05 TSCA ST CE is compliant with the preconditions for use in BREEAM 2016 certified buildings and fulfils the emission requirements at exemplary level. Beyond that the usage of this product may contribute to gather additional points within the BREEAM scoring system. The following table shows all BREEAM credits which are applicable to the usage of our product. As the actually achievable number of credits depends on the attributes of all used materials in the BREEAM building project and further actions by the constructor, we cannot guarantee to obtain the maximum score. For full requirement terms see BREEAM manual at [www.breeam.com](http://www.breeam.com).

| Requirements  |  |                 | Product contributions  |
|---|--|-----------------|--|
| Chapter   | Requirement summary  | Maximum Credits |  |
| <b>Mat 01</b><br><b>Life cycle impacts</b>                            | Environmental product declarations (EPD) – product installed by Post-Construction Stage is covered by verified EPD   | 1<br>Credits    | This product has a verified Environmental Product Declaration (EPD) according to ISO 14025 and EN 15804. See <ul style="list-style-type: none"> <li>Environmental Product Declaration (EPD) MDF raw boards (Pdf)</li> </ul> available for download at <a href="http://www.egger.com/environment">www.egger.com/environment</a>   |
| <b>Mat 03</b><br><b>Responsible sourcing of construction products</b> | All timber-based products used on the project are Legally harvested and traded timber.   | Prerequisite    | The products is verified by the ISO 38200 : 2018 statements. This standard takes into account all legal requirements in the respective purchasing or production country and all environmental and social criteria known in the ISO system. Additionally, the product can be purchased in other certified qualities on request. Use delivery receipt as evidence document. See also chapter “Wood origin” of this document. |
| <b>Hea 02</b><br><b>Indoor air quality</b>                            | Avoidance of asbestos.   | Prerequisite    | The product complies with this prerequisite. See <ul style="list-style-type: none"> <li>Manufacturer's Declaration – Asbestos (Pdf)</li> </ul> available for download at <a href="http://www.egger.com/environment">www.egger.com/environment</a>  |
| <b>Hea 02</b><br><b>Indoor air quality</b>                            | Minimizing sources of pollution - Emissions from building products. Product should meet the exemplary level emission criteria<br>Formaldehyde $\leq 0.08 \text{ mg/m}^3$<br>TVOC $\leq 1.0 \text{ mg/m}^3$<br>Category 1A and 1B carcinogens $\leq 0.001 \text{ mg/m}^3$ | 1<br>Credit     | <i>Product does not meet the exemplary level emissions criteria as a raw board. Use laminated material e.g. EGGER Eurodekor MDF to gather full credits.</i>  |

## Compliance with DGNB Gebäude Neubau2018

As the DGNB certification system is primarily relevant for projects in the German-speaking countries, this chapter is given in German language.

Die DGNB Auszeichnungen Silber, Gold und Platin ergeben sich aus den Gesamterfüllungsgrad des Bauprojektes. Welche Qualitätsstufen das Produkt EGGER MDF E1E05 TSCA ST CE nach dem DGNB-System erfüllt und wo Sie die benötigten Nachweise finden, können Sie der folgenden Tabelle entnehmen. Die Beiträge zum Gesamterfüllungsgrad, die sich nach dem DGNB Punktesystem hieraus ergeben, hängen u.a. von der Relevanz der Produktgruppe für das Gesamtgebäude ab. Bitte beachten Sie, dass für die Gesamtbewertung des Gebäudes darüber hinaus noch weitere Kriterien von Bedeutung sind. Eine durch den Einsatz der Produktes EGGER MDF E1E05 TSCA ST CE zu erhaltende Punktzahl können wir daher nicht garantieren.

| Themenfeld  | Kriterien   |                                      | Beitrag des Produktes   |
|---|---|--------------------------------------|---|
|   | Zusammenfassung Kriterium   | Qualitätsstufe/<br>Bonus             |   |
| ENV1.1<br>Ökobilanz des Gebäudes                  | Die Gebäude-Ökobilanz benötigt Baustoffdaten. Produktspezifische Daten (EPDs) werden bevorzugt.   | -                                    | Für das Produkt liegt eine Umweltproduktdeklaration (EPD) vor. Sie finden das Dokument <ul style="list-style-type: none"> <li>EPD EGGER MDF roh DE (Pdf)</li> </ul> im Downloadbereich auf <a href="http://www.egger.com/umwelt">www.egger.com/umwelt</a> .   |
| ENV1.2<br>Risiken für die lokale Umwelt           | Formaldehydgrenzwert für Holzwerkstoffe in Aufenthaltsräumen:<br>RAL UZ 76 oder Formaldehyd <0,05 ppm in Prüfkammer.  | 4                                    | Der Grenzwert wird eingehalten. Das Produkt hält die Anforderungen der deutschen ChemVerbotsVO ein (E0,5). Bitte wenden Sie sich an unseren Verkaufsservice, um einen aktuellen Formaldehydprüfbericht (Pdf) zu erhalten.   |
| ENV1.3<br>Verantwortungsvolle Ressourcengewinnung | Zertifizierte verantwortungsbewusste Ressourcengewinnung eines Teils der Wertschöpfungskette.   | 1.2                                  | Die Lieferkette von Holz und Papier sind nach ISO 38200 (Chain-of Custody, CoC) zertifiziert. Die Norm berücksichtigt alle Legalitätsanforderungen im jeweiligen Einkaufs- bzw. Produktionsland und alle im ISO System bekannten Umwelt- und Sozialkriterien. Sie finden das Dokument <ul style="list-style-type: none"> <li>Herstellereklärung über die Holzherkünfte (Pdf)</li> </ul> im Downloadbereich auf <a href="http://www.egger.com/umwelt">www.egger.com/umwelt</a> . |
| TEC1.6<br>Rückbau- und Recyclingfreundlichkeit    | Indikator 1 Recyclingfreundliche Materialauswahl:<br>Stoffliche Verwertung  | 2                                    | Das Produkt besteht zu 66% aus Sägenebenprodukten. Nutzen Sie als Nachweis die die Informationen der Spalte 5 „Co-products content in %“ aus der <ul style="list-style-type: none"> <li>Herstellereklärung über die Holzherkünfte (Pdf)</li> </ul> im Downloadbereich auf <a href="http://www.egger.com/umwelt">www.egger.com/umwelt</a> .  |
| TEC1.6<br>Rückbau- und Recyclingfreundlichkeit    | Im Gebäude werden Bauteile eingesetzt, die heute bereits nachweislich einer <b>werkstofflichen</b> Verwertung zu einem vergleichbaren Produkt zugeführt werden. | Max. 1 Punkt<br>CE Bonus pro Bauteil | MDF-Platten können in geringen Mengen im Altholzstrom toleriert werden, aber nicht als alleinige Quelle für die Produktion neuer Spanplatten dienen.  |



## Compliance with Nordic Swan Ecolabel

### Small houses, apartment buildings and buildings for schools and pre-schools

The product EGGER MDF E1E05 TSCA ST CE is listed in the database for building products that can be used in Nordic Swan Ecolabelled buildings (Portal Nordic Ecolabelling) under the Manufacturer's name Egger, Fritz GmbH & Co. As an applicant for an Ecolabelled building, please inform your Nordic Swan certifier about the product listing. For the use of EGGER MDF E1E05 TSCA ST CE no other documents are necessary for your application.

### Furniture and Fitments, version 4.15

If you are planning to certify a furniture product with the Nordic Swan Ecolabel, we as your supplier are happy to provide you with the required evidence documents, as shown below. From our current knowledge, all other requirements beyond this list are not applicable to this product from the raw material supplier. When in doubt, please always take the original criteria version as a reference at the official Nordic Swan website.

| Requirements                               |   | Product contributions   |
|--|---|---|
| Chapter                                    | Requirement summary   |   |
| <b>R11 Origin and traceability</b>         | Written procedure ensuring traceability to the origin of the raw materials  | The product complies with the requirement. The following evidence document can be used: <ul style="list-style-type: none"> <li>▪ Certificate ISO 38200:2018 (Pdf)</li> </ul> available for download at <a href="http://www.egger.com/environment">www.egger.com/environment</a> .                         |
| <b>R12 Chemical products and additives</b> | Chemical products and additives/constituent substances used in the production of wood-based panels must satisfy the requirements of R3, R4 and R5 in Chapter 2.1. | The product complies with the requirement. Please get in touch with the EGGER product sustainability & compliance team at <a href="mailto:environment@egger.com">environment@egger.com</a> to get Form 2a documents and safety data sheets for each chemical product and additive/ constituent substance. |
| <b>R13 Formaldehyde</b>                    | Average emissions of formaldehyde must not exceed 124 µg/m³ air as determined by the current version of EN 717-1  | The product complies with the requirement. Please get in touch with the EGGER product sustainability & compliance team at <a href="mailto:environment@egger.com">environment@egger.com</a> to get EGGER MDF E1E05 TSCA ST CE Formaldehyde test report (Pdf).  |

## Compliance with other labels & regulations

Additional information in the form of manufacturer declarations, EPDs and brochures is available at

- [www.egger.com/environment](http://www.egger.com/environment)

Your label or regulation is missing? The EGGER product sustainability & compliance team is happy to support you with suitable information on the requirements. Please get in touch with

- [environment@egger.com](mailto:environment@egger.com)

or contact your EGGER sales contact or distributor, who are happy to forward the inquiry.

## Footnotes

i

| Production plant | Address   |
|------------------|---|
| Gagarin, RU      | OOO "EGGER Drevprodukt Gagarin", Ezhvinsky proezd 1, 215010 Gagarin, Oblast Smolensk (RU) |
| Brilon, D        | EGGER Holzwerkstoffe Brilon GmbH & Co. KG, Im Kissen 19, 59929 Brilon (DE)                |

ii

| Product Certifications |   |
|------------------------|---|
| ISO 38200:2018         | ISO 38200:2018 Chain of Custody of wood and wood-based products |

iii

| Substance    | Norm   | Limit value   | Testing method                  | Accredited testing institute     |
|--------------|--|---|---------------------------------|----------------------------------|
| Formaldehyde | According to EN 13986+A1:2015-04, Formaldehyde class E1                                      | 0.1ppm  | EN 717-1                        | Fraunhofer WKI, Braunschweig (D) |
| Formaldehyde | German Chemical Prohibition Ordinance (ChemVerbotsV) 2020                                    | 0.05 ppm, test results are multiplied by the factor 2 | EN 16516:2017+A1:2020/ EN 717-1 | Fraunhofer WKI, Braunschweig (D) |
| Formaldehyde | California's Composite Wood Products Regulation (CWP Regulation) Phase 2                     | 0.11 ppm  | ASTM D6007-14                   | Fraunhofer WKI, Braunschweig (D) |
| Formaldehyde | U.S. Toxic Substances Control Act (TSCA), requirements of EPA TSCA Title VI – § 770.10 b 1-4 | 0.11 ppm  | ASTM D6007-14                   | Fraunhofer WKI, Braunschweig (D) |