







TECHNICAL DATASHEET	
EGGER HOME DESIGN	CLASSIC
Coreboard	 UWF [®] Ultra Wood Fibre
Profil	 The patented UNI fit! installation system stands for a quick and simple installation process. Produced under the licence of Flooring Industries™.
Guarantee domestic area	 according to Egger Guarantee
Guarantee comercial area	 according to Egger Guarantee
Antistatic properties according EN1815	 no
Class of use	32
European Norm	 EN16511:2014
Format	Classic
Dimension mm (length x width)	1295 x 192
Complete thickness	5
Integrated underlay	-
Bevel	WV4
Pallet	Packaging
Paket information	Euro
	Piece 8
	m2 1,99
	kg 9,25
Pallet information	
	Piece 480
	m2 119,35
	kg 617
test methode	Classification and general requirements according to EN 16511:2014
abrasion resistance (testA) according EN 13329, annex E	AC4 (IP ≥ 1200)
impact resistance according EN13329, annex F	≥ 1200 mm
Micro scratch resistance according to EN16094	<MSR-A3 <MSR-B3
Effect of a castor chair according EN425	No change in appearance or damage
Effect of furniture leg according EN424	No damage shall be visible, when tested with foot Type 0 artefact
resistance to staining EN 438 - 2	group 1 + 2: level 5 group 3: level 4
Thickness swelling according ISO 24336	≤ 5 % (+1%)
bonding strength [kN/m] according ISO 24334	length side > 1,0 narrow side > 2,0
tolerance of top layer according ISO 24337	length ± 0,5 mm width ± 0,1 mm thickness ± 0,5 mm
Dimensional changes due to temperature changes according EN ISO 23999	< 0,25%
Static indentation by constant pressure according EN ISO 24343-1	≤ 0,2 mm

disposal key: 170201/030103, municipal law 200138 (varietal purity) or 200307 (bulky waste)

