







TECHNICAL DATASHEET		
EGGER HOME COMFORT		Classic
Coreboard		HDF swell stopp plus
Profil		The CLIC it! installation system stands for a customizable and safety installation.
Guarantee domestic area		according to Egger Guarantee
Guarantee comercial area		according to Egger Guarantee
Antistatic properties according EN1815		not available
Class of use	31	
European Norm	 EN 16511-31	
Format	CLASSIC	
Dimension mm (length x width)	1292 x 193	
Complete thickness	8	
Integrated underlay	yes, made from natural cork	
Bevel	WV4	-
Packaging		
Pallet	Euro	
Paket information		
	Piece	8
	m2	1,59
	kg	12,97
Pallet information		
	Piece	384
	m2	95,75
	kg	653,00
Classification and general requirements according to EN16511:2014		
abrasion resistance according EN13329, Annex E	AC3 (IP ≥ 600)	
impact resistance according EN13329, Annex F	≥ 800 mm	
resistance to staining EN 438 - 2	group 1 + 2: level 4 group 3: level 3	
Thickness swelling according ISO 24336	≤ 20 %	
tolerance of top layer according ISO 24337	length ± 0,5 mm width ± 0,1 mm thickness ± 0,5 mm	
Static indentation by constant pressure according EN24343-1 (EN/ISO)	≤ 0,3	
Effect of a castor chair according EN425	10.000 cycles	
Thermal resistance according to EN 12667	0,09m2 K/W	
Impact Sound Reduction according to EN ISO 10140 -3	≤16 dB	
Room Sound Reduction IHD W 431	47% (1)	

* reference flooring construction: 7 mm laminate flooring on 3 mm PE-Foam and 0,2 mm PE-Film
The determined room sound improvement gives the percentage reduction of the loudness feeling relating to the reference.



www.blauer-engel.de/uz176

- low emissions and pollutants
- wood from sustainable forestry
- no adverse impact on health in the living environment

TECHNICAL DATASHEET	
EGGER HOME COMFORT	Large
Coreboard	HDF swell stopp plus
Profil	The CLIC it! installation system stands for a customizable and safety installation.
Guarantee domestic area	according to Egger Guarantee
Guarantee comercial area	according to Egger Guarantee
Antistatic properties according EN1815	not available
Class of use	31
European Norm	EN 16511-31
Format	Large
Dimension mm (length x width)	1292 x 245
Complete thickness	8
Integrated underlay	yes, made from natural cork
Bevel	WV4
	Packaging
Pallet	One-way-pallet
Paket information	
Piece	8
m2	2,02
	39
kg	675,00
Pallet information	
Piece	312
m2	98,76
kg	705,00
Classification and general requirements according to EN16511:2014	
abrasion resistance according EN13329, Annex E	IP ≥ 600 cycles
impact resistance according EN13329, Annex F	≥ 800 mm
resistance to staining EN 438 - 2	group 1 + 2: level 4 group 3: level 3
Thickness swelling according ISO 24336	≤ 20 %
tolerance of top layer according ISO 24337	length ± 0,5 mm width ± 0,1 mm thickness ± 0,5 mm
Static indentation by constant pressure according EN24343-1 (EN/ISO)	≤ 0,3
Effect of a castor chair according EN425	10.000 cycles
Thermal resistance according to EN 12667	0,09m2 K/W
Impact Sound Reduction according to EN ISO 10140 -3	≤16 dB
Room Sound Reduction IHD W 431	47% (1)

* reference flooring construction: 7 mm laminate flooring on 3 mm PE-Foam and 0,2 mm PE-Film
The determined room sound improvement gives the percentage reduction of the loudness feeling relating to the reference.



TECHNICAL DATASHEET	
EGGER HOME COMFORT Kingsize	
Coreboard	HDF swell stopp plus
Profil	The CLIC it! installation system stands for a customizable and safety installation.
Guarantee domestic area	according to Egger Guarantee
Guarantee comercial area	according to Egger Guarantee
Antistatic properties according EN1815	not available
Class of use	31
European Norm	EN 16511-31
Format	Large
Dimension mm (length x width)	1292 x 327
Complete thickness	8
Integrated underlay	yes, made from natural cork
Bevel	WW4
Packaging	
Pallet	Euro
Paket information	
Piece	6
m2	2,68
kg	627,00
Pallet information	
Piece	228
m2	96,33
kg	657,00
Classification and general requirements according to EN16511:2014	
abrasion resistance according EN13329, Annex E	IP ≥ 600 cycles
impact resistance according EN13329, Annex F	≥ 800 mm
resistance to staining EN 438 - 2	group 1 + 2: level 4 group 3: level 3
Thickness swelling according ISO 24336	≤ 20 %
tolerance of top layer according ISO 24337	length ± 0,5 mm width ± 0,1 mm thickness ± 0,5 mm
Static indentation by constant pressure according EN24343-1 (EN/ISO)	≤ 0,3
Effect of a castor chair according EN425	10.000 cycles
Thermal resistance according to EN 12667	0,09m2 K/W
Impact Sound Reduction according to EN ISO 10140 -3	≤16 dB
Room Sound Reduction IHD W 431	47% (1)

* reference flooring construction: 7 mm laminate flooring on 3 mm PE-Foam and 0,2 mm PE-Film
The determined room sound improvement gives the percentage reduction of the loudness feeling relating to the reference.



www.blauer-engel.de/uz176

- low emissions and pollutants
- wood from sustainable forestry
- no adverse impact on health in the living environment