

MORE FROM WOOD.



TECHNICAL DATASHEET		
EGGER PRO COMFORT		Classic
Coreboard	E1 HCHO	HDF swell stopp plus
Profil	UNI fit	The patented UNI fit! installation system stands for a quick and simple installation process without glue. Produced under the licence of Flooring Industries™.
Guarantee domestic area	15	according to Egger Guarantee
Guarantee comercial area	5	according to Egger Guarantee
Antistatic properties according EN1815	7	not available
Class of use	31	
European Norm	EN 16511-31	
Format	CLASSIC	
Dimension mm (length x width)	1292 x 193	
Complete thickness	10	
Integrated underlay	yes, made from natural cork	
Bevel	WV4	
	Packaging	
Pallet	One-way-pallet	
Paket information		
	Piece	7
	m2	1,75
	kg	14,22
Pallet information		
	Piece	336
	m2	83,78
	kg	702,00
Classification and general requirements according to EN16511		
abrasion resistance, test methode A according EN13329, Annex E	IP ≥ 600 cycles	
impact resistance, test methode "big ball" according EN13329, Annex H	≥ 800 mm	
resistance to staining EN 438 - 2	group 1 + 2: level 4 group 3: level 3	
Thickness swelling according ISO 24336	≤ 20 %	
tolerance of top layer according ISO 24337	length ± 0,5 mm width ± 0,1 mm thickness ± 0,5 mm	
Static indentation by constant pressure according EN24343-1 (EN/ISO)	≤ 0,3 mm	
Effect of a castor chair according EN425	10.000 cycles	
Thermal resistance according to EN 12667	0,09 m2 K/W	
Impact Sound Reduction according to EN ISO 10140 -3	≤ 16 dB	
Room Sound Reduction IHD W 431	≤ 43% (1)	

* reference flooring construction: 7 mm laminate flooring on 3 mm PE Foam and 0,2 mm PE-Film. The determined room sound improvement gives the percentage reduction of the loudness feeling relating to the reference.



TECHNICAL DATASHEET		
EGGER PRO COMFORT		Large
Coreboard	E1 HCHO	HDF swell stopp plus
Profil	UNI fit PATENTED	The patented UNI fit! installation system stands for a quick and simple installation process without glue. Produced under the licence of Flooring Industries™.
Guarantee domestic area	15 years	according to Egger Guarantee
Guarantee comercial area	5 years	according to Egger Guarantee
Antistatic properties according EN1815		not available
Class of use	31	
European Norm	EN 16511-31	
Format	Large	
Dimension mm (length x width)	1292 x 245	
Complete thickness	10	
Integrated underlay	yes, made from natural cork	
Bevel	WV4	
Packaging		
Pallet	One-way-pallet	
Paket information		
	Piece	7
	m2	2,21
	kg	18,09
Pallet information		
	Piece	273
	m2	86,19
	kg	725,00
Classification and general requirements according to EN16511		
abrasion resistance, test methode A according EN13329, Annex E	IP ≥ 600 cycles	
impact resistance, test methode "big ball" according EN13329, Annex H	≥ 800 mm	
resistance to staining EN 438 - 2	group 1 + 2: level 4 group 3: level 3	
Thickness swelling according ISO 24336	≤ 20 %	
tolerance of top layer according ISO 24337	length ± 0,5 mm width ± 0,1 mm thickness ± 0,5 mm	
Static indentation by constant pressure according EN24343-1 (EN/ISO)	≤ 0,3 mm	
Effect of a castor chair according EN425	10.000 cycles	
Thermal resistance according to EN 12667	0,09 m2 K/W	
Impact Sound Reduction according to EN ISO 10140 -3	≤ 16 dB	
Room Sound Reduction IHD W 431	≤ 43% (1)	

*reference flooring construction: 7 mm laminate flooring on 3 mm PE Foam and 0,2 mm PE Film. The determined room sound improvement gives the percentage reduction of the loudness feeling relating to the reference.



TECHNICAL DATASHEET		
EGGER PRO COMFORT		Kingsize
Coreboard	E1 HCHO	HDF swell stopp plus
Profil	UNI fit! PATENTED	The patented UNI fit! installation system stands for a quick and simple installation process without glue. Produced under the licence of Flooring Industries™.
Guarantee domestic area	15 Y	according to Egger Guarantee
Guarantee comercial area	5 Y	according to Egger Guarantee
Antistatic properties according EN1815	7	not available
Class of use	31	
European Norm	EN 16511-31	
Format	Kingsize	
Dimension mm (length x width)	1292 x 327	
Complete thickness	10	
Integrated underlay	yes, made from natural cork	
Bevel	WV4	
Pallet	Packaging One-way-pallet	
Paket information		
	Piece	5
	m2	2,11
	kg	17,49
Pallet information		
	Piece	200
	m2	84,4
	kg	720
Classification and general requirements according to EN16511		
abrasion resistance, test methode A according EN13329, Annex E	IP ≥ 600 cycles	
impact resistance, test methode "big ball" according EN13329, Annex H	≥ 800 mm	
resistance to staining EN 438 - 2	group 1 + 2: level 4 group 3: level 3	
Thickness swelling according ISO 24336	≤ 20 %	
tolerance of top layer according ISO 24337	length ± 0,5 mm width ± 0,1 mm thickness ± 0,5 mm	
Static indentation by constant pressure according EN24343-1 (EN/ISO)	≤ 0,3 mm	
Effect of a castor chair according EN425	10.000 cycles	
Thermal resistance according to EN 12667	0,09 m2 K/W	
Impact Sound Reduction according to EN ISO 10140 -3	≤ 16 dB	
Room Sound Reduction IHD W 431	≤ 43% (1)	

*reference flooring construction: 7 mm laminate flooring on 3 mm PE-Foam and 0,2 mm PE-Film. The determined room sound improvement gives the percentage reduction of the loudness feeling relating to the reference.



TECHNICAL DATASHEET		
EGGER PRO COMFORT		Long
Coreboard	E1 HCHO	HDF swell stopp plus
Profil	UNI FIT PATENTED	The patented UNI fit! installation system stands for a quick and simple installation process without glue. Produced under the licence of Flooring Industries™.
Guarantee domestic area	15 years	according to Egger Guarantee
Guarantee comercial area	5 years	according to Egger Guarantee
Antistatic properties according EN1815	Antistatic	not available
Class of use	31	
European Norm	EN 16511-31	
Format	Long	
Dimension mm (length x width)	2050 x 245	
Complete thickness	10	
Integrated underlay	yes, made from natural cork	
Bevel	WV4	
Pallet	Packaging One-way-pallet	
Paket information		
	Piece	5
	m2	2,51
	kg	21,19
Pallet information		
	Piece	165
	m2	82,83
	kg	719
Classification and general requirements according to EN16511		
abrasion resistance, test methode A according EN13329, Annex E	IP ≥ 600 cycles	
impact resistance, test methode "big ball" according EN13329, Annex H	≥ 800 mm	
resistance to staining EN 438 - 2	group 1 + 2: level 4 group 3: level 3	
Thickness swelling according ISO 24336	≤ 20 %	
tolerance of top layer according ISO 24337	length ± 0,3 mm width ± 0,1 mm thickness ± 0,5 mm	
Static indentation by constant pressure according EN24343-1 (EN/ISO)	≤ 0,3 mm	
Effect of a castor chair according EN425	10.000 cycles	
Thermal resistance according to EN 12667	0,09 m2 K/W	
Impact Sound Reduction according to EN ISO 10140 -3	≤ 16 dB	
Room Sound Reduction IHD W 431	≤ 43% (1)	

* reference flooring construction: 7 mm laminate flooring on 3 mm PE-Foam and 0,2 mm PE-Film. The determined room sound improvement gives the percentage reduction of the loudness feeling relating to the reference.

