

**TECHNICAL DATASHEET**

EGGER PRO LAMINATE FLOORING		8/32 Kingsize WV4 CLIC it!
Core board	E1 HCHO	HDF swell stopp plus
Locking system	CLIC it!	The CLIC it! installation system means flexible and secure installation.
Warranty	20	20 years limited residential warranty according to the warranty declaration of Egger Flooring International GmbH & Co.KG
Warranty time residential area	5	5 years limited commercial warranty according to the warranty declaration of EGGER Flooring International GmbH & Co. KG
Antistatic properties according to EN1815	Antistatic	yes, ≤ 2 kV
Class of use	32	
European Standard EN13329	EN 13329-32	
Format	KINGSIZE	
Dimension (length x width) in mm / inch	1291 x 327 mm / 50.87 x 12.87 inch	
Overall thickness	8 mm	
Bevel	WV4 (4-sided bevel)	
Pallet	Packaging One-way-pallet	
Paket information		
	Planks per Box	6
	m <sup>2</sup> / ft <sup>2</sup>	2,53/ 27.29
	kg / lbs	18,96 / 41.79
Pallet information		
	Planks per Pallet	240
	m <sup>2</sup> / ft <sup>2</sup>	101,40 / 1091.43
	kg / lbs	794,0 / 1,750.47
Classification and general requirements according EN13329		
Abrasion Resistance according to EN13329 (annex E)	AC4 (IP ≥ 4000)	
Impact resistance according to EN13329 (annex H)	Big ball: ≥ 750 mm / ≥ 29.53 inch Small ball: ≥ 12 N	
Resistance according to EN438	Group 1 + 2: level 5 group 3: level 4	
Effect of furniture leg according to EN424	No damage shall be visible, when tested with foot Type 0 artefact	
Effect of a castor chair according to EN425 (Type W)	No change in appearance or damage	
Thickness swelling according to ISO 24336	≤ 18 %	
Tolerance of surface layer according to EN13329	length ± 0,5 mm / ± 0.019 inch width ± 0,1 mm / ± 0.0039 inch	
Tolerance of the thickness of the element according to EN13329	thickness ± 0,5 mm / ± 0.019 inch	
Light fastness according to EN13329	gray scale ≥ level 4 (EN:20105-A02)	
Static indentation by constant pressure according to EN ISO 24343-1	≤ 0.05	
Surface soundness according to EN13329, annex D	≥ 1.25 N/mm <sup>2</sup> / ≥ 0.0019 inch <sup>2</sup>	
Thermal resistance according to EN12667	~ 0,08 m <sup>2</sup> K/W	
Slip resistance according to EN13893	DS	
Fire classification according to ASTM E648	Class 1	



**WARNING:** This product can expose you to chemicals including Formaldehyde which is known to the State of California to cause cancer. For more information go to HYPERLINK: [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)  
Drilling, sawing or machining wood products generates wood dust, a substance known to cause cancer. Avoid inhaling wood dust or use a NIOSH-approved half-mask respirator, side shielded safety glasses and other safeguards for personal protection.

