


TECHNICAL DATASHEET		
EGGER HOME COMFORT		Classic
Coreboard		HDF swell stopp plus
Profil		The patented UNI fit! installation system stands for a quick and simple installation process without glue. Produced under the licence of Flooring Industries™.
Guarantee domestic area		according to Egger Guarantee
Guarantee comercial area		according to Egger Guarantee
Antistatic properties according EN1815		not available
Class of use		31
European Norm		 EN 16511-31
Format		CLASSIC
Dimension mm (length x width)		1292 x 193
Complete thickness		8
Integrated underlay		Thermal resistance according to EN 12667
Bevel		WW4
Pallet		Packaging Euro
Paket information		
	Piece	8
	m2	1,99
	kg	12,97
Pallet information		
	Piece	384
	m2	95,75
	kg	653,00
Classification and general requirements according to EN16511:2014		
abrasion resistance according EN13329, Annex E		AC3 (IP ≥ 600)
impact resistance according EN13329, Annex F		≥ 800 mm
resistance to staining EN 438 - 2		group 1 + 2: level 4 group 3: level 3
Thickness swelling according ISO 24336		≤ 20 %
tolerance of top layer according ISO 24337		length ± 0,5 mm width ± 0,1 mm thickness ± 0,5 mm
Static indentation by constant pressure according EN24343-1 (EN/ISO)		≤ 0,3
Effect of a castor chair according EN425		10.000 cycles
Thermal resistance according to EN 12667		0,09m2 K/W
Impact Sound Reduction according to EN ISO 10140 -3		≤16 dB
Room Sound Reduction IHD W 431		47% (1)

* reference flooring construction: 7 mm laminate flooring on 3 mm PE-Foam and 0,2 mm PE-Film
The determined room sound improvement gives the percentage reduction of the loudness feeling relating to the reference.

