







| TECHNICAL DATASHEET | | |
|--|--|--|
| Egger Home Laminate Flooring | | 8/32 Classic WV4 |
| Coreboard |  | HDF swell stopp plus |
| Profile |  | The patented UNI fit! installation system stands for a quick and simple installation process without glue. Produced under the licence of Flooring Industries™. |
| Guarantee domestic area |  | according to Egger Guarantee |
| Guarantee comercial area |  | according to Egger Guarantee |
| Antistatic properties according EN1815 |  | yes, < 2 kV |
| Class of use | 32 | |
| European Norm EN13329 |  | |
| Format | CLASSIC | |
| Dimension mm (length x width) | 1291 x 193 | |
| Complete thickness | 8 | |
| Thickness of silenzio® special cellulose Bevel | WV4 | |
| Pallet | Packaging Euro | |
| Paket information | | |
| | Piece | 8 |
| | m2 | 1,99 |
| | kg | 14,46 |
| Pallet information | | |
| | Piece | 480 |
| | m2 | 119,40 |
| | kg | 877,00 |
| Classification and general requirements according EN13329 | | |
| Abrasion resistance according EN13329, annex E | AC4 (IP ≥ 4000) | |
| Impact resistance according EN13329, annex H | Big ball: ≥ 750 mm Small ball: ≥ 12 N | |
| Resistance to staining EN438 | Group 1 + 2: level 5 group 3: level 4 | |
| Effect of furniture leg according EN424 | No damage shall be visible, when tested with foot Type 0 artefact | |
| Effect of a castor chair according EN425 (Type W) | No change in appearance or damage | |
| Thickness swelling according ISO 24336 | ≤ 18 % | |
| Tolerance of top layer according EN13329 | length ± 0,5 mm width ± 0,1 mm thickness ± 0,5 mm | |
| Light fastness according EN13329 | grey scale ≥ level 4 (EN:20105-A02) | |
| Static indentation by constant pressure according EN ISO 24343-1 | < 0,05 | |
| Surface soundness according EN13329, annex D | ≥ 1,25 N/mm ² | |
| Thermal resistance according to EN 12667 | 0,07 m ² K/W | |

