

TECHNICAL DATASHEET	
EGGER PRO LAMINATE FLOORING	
8/33 Aqua Plus	
Coreboard	HDF Aqua Plus
Profile	The patented UNI fit! installation system stands for a quick and simple installation process without glue. Produced under the licence of Flooring Industries™.
Guarantee domestic area	according to Egger Guarantee
Guarantee commercial area	according to Egger Guarantee
Antistatic properties according EN1815	yes, < 2 kV
Class of use	33
European Norm EN13329	EN 13329-33
Format	CLASSIC
Dimension mm (length x width)	1291 x 193
Complete thickness	8
Thickness of silenzio® special cellulose	
Bevel	WV4
Pallet	Packaging One-way-pallet
Paket information	
Piece	8
m <sup>2</sup>	1,99
kg	14,78
Pallet information	
Piece	480
m <sup>2</sup>	119,60
kg	910,00
Classification and general requirements according EN13329	
Abrasion resistance according EN13329, annex E	AC5 (IP ≥ 6000)
Impact resistance according EN13329, annex H	Big ball: ≥ 1000 mm Small ball: ≥ 15 N
Resistance to staining EN438	Group 1 + 2: level 5 group 3: level 5
Effect of furniture leg according EN424	No damage shall be visible, when tested with foot Type 0 artefact
Effect of a castor chair according EN425 (Type W)	No change in appearance or damage
Thickness swelling according ISO 24336	≤ 5 % (+/-1)
Tolerance of top layer according EN13329	length ± 0,5 mm width ± 0,1 mm thickness ± 0,5 mm
Light fastness according EN13329	grey scale ≥ level 4 (EN:20105-A02)
Static indentation by constant pressure according EN ISO 24343-1	< 0,05
Surface soundness according EN13329, annex D	≥ 1,25 N/mm <sup>2</sup>
Thermal resistance according to EN 12667	0,06 m <sup>2</sup> K/W

