













TECHNICAL DATASHEET		
EGGER HOME Design Flooring GreenTec		CLASSIC
Coreboard		GreenTec Board
Profil		The CLIC it! installation system stands for a customizable and safety installation.
Guarantee domestic area		according to Egger Guarantee
Guarantee commercial area		according to Egger Guarantee
Antistatic properties according EN1815		no
Class of use		33
European Norm		 EN 16511-33
Format		Classic
Dimension mm (length x width)		1292 x193
Complete thickness		7,5 mm
Integrated underlay		0,9 mm cork
Bevel		WV4
Pallet		Packaging
Paket information		One-way-pallet
	Piece	8
	m2	1,99
	kg	13,16
	Piece	448
	m2	111,71
	kg	736,96
test methode		Classification and general requirements according to EN 16511:2014
abrasion resistance (testA) according EN 13329, annex E		AC5 (IP ≥ 2000)
impact resistance according EN13329, annex F		≥ 1600 mm
Micro scratch resistance according to EN16094		≤MSR-A2
Effect of a castor chair according EN425		25.000 cycles, no change in appearance or damage
Effect of furniture leg according EN424		No damage shall be visible, when tested with foot Type 0 artefact
resistance to staining EN 438 - 2		group 1 + 2: level 5 group 3: level 4
Thickness swelling according ISO 24336		≤ 5 % (+1%)
bonding strength [kN/m] according ISO 24334		length side > 1,0 narrow side > 2,0
tolerance of top layer according ISO 24337		length ± 0,5 mm width ± 0,1 mm thickness ± 0,5 mm
Dimensional changes due to temperature changes according EN ISO 23999		< 0,25%
Static indentation by constant pressure according EN ISO 24343-1		≤ 0,2 mm
Thermal resistance according to EN 12667		0,05m2 K/W
Impact Sound Reduction according to EN ISO 10140 - 3		18dB
Room Sound Reduction IHD W 431		34%



TECHNICAL DATASHEET		
EGGER HOME Design Flooring <i>GreenTec</i>		LARGE
Coreboard		GreenTec Board
Profil		The CLIC it! installation system stands for a customizable and safety installation.
Guarantee domestic area		according to Egger Guarantee
Guarantee commercial area		according to Egger Guarantee
Antistatic properties according EN1815		no
Class of use		33
European Norm		
Format		Large
Dimension mm (length x width)		1292 x246
Complete thickness		7,5 mm
Integrated underlay		0,9 mm cork
Bevel		WV4
Pallet		Packaging One-way-pallet
Paket information		
	Piece	8
	m2	1,99
	kg	16,76
Pallet information		
	Piece	336
	m2	106,79
	kg	704,31
test methode		Classification and general requirements according to EN 16511:2014
abrasion resistance (testA) according EN 13329, annex E		AC5 (IP ≥ 2000)
impact resistance according EN13329, annex F		≥ 1600 mm
Micro scratch resistance according to EN16094		≤MSR-A2
Effect of a castor chair according EN425		25.000 cycles, no change in appearance or damage
Effect of furniture leg according EN424		No damage shall be visible, when tested with foot Type 0 artefact
resistance to staining EN 438 - 2		group 1 + 2: level 5 group 3: level 4
Thickness swelling according ISO 24336		≤ 5 % (+1%)
bonding strength [kN/m] according ISO 24334		length side > 1,0 narrow side > 2,0
tolerance of top layer according ISO 24337		length ± 0,5 mm width ± 0,1 mm thickness ± 0,5 mm
Dimensional changes due to temperature changes according EN ISO 23999		< 0,25%
Static indentation by constant pressure according EN ISO 24343-1		≤ 0,2 mm
Thermal resistance according to EN 12667		0,05 m2 K/W
Impact Sound Reduction according to EN ISO 10140 -3		18dB
Room Sound Reduction IHD W 431		34%

