

QUALITY MANAGEMENT ISO 9001:2008

Codierung: TD SKIRTING EN
ID3184
Revision: 02
Date: 09.11.2018

TECHNICAL DATASHEET

EGGER Skirting

Application area

Preparation of wall endings after installation of EGGER flooring

Material data

Parameter	Unit							
Surface		Melamin-/ urea impregnated decor paper						
Carrier material		MDF (medium density fibreboard)						
Product		Beading profile 1,6 cm with adhesive strip	Skirting 6 cm	Skirting 6 cm cubic	Skirting 7 cm	Skirting 8 cm	Skirting 9,5 cm	Skirting 10 cm
Profile drawing								
Length	mm	2400	2400	2400	2400	2400	2400	2400
Thickness	mm	16	17	16	18	14	15	18
Width	mm	16	60	58	70	80	95	100
Colour		see decor list skirting		white	white	see decor list skirting	white	white
Paintable		No	no	yes, lacquering with acrylic lacquer or solvent-free lacquers before installation is recommended	no	yes, lacquering with acrylic lacquer or solvent-free lacquers before installation is recommended		

Product		Beading profile 1,6 cm with adhesive strip	Skirting 6 cm	Skirting 6 cm cubic	Skirting 7 cm	Skirting 8 cm	Skirting 9,5 cm	Skirting 10 cm
Skirting per package	piece	25	10	8	8	5	8	6
Meter per package	m	60	24	19,2	19,2	12	19,2	14,4
Skirting per pallet	piece	600	400	320	320	360	288	180
Meter per pallet	m	1440	960	768	768	864	691,2	432
Method of use		self adhesive	Clipstar (distance 25-50 cm depending on the wall construction)	-adhesive (SMP constructio n adhesive or 1K PU adhesive) -tacking (compress ed-air tacker)	Clipstar (distance 25-50 cm depending on the wall construction)		-adhesive (SMP construction adhesive or 1K PU adhesive) -tacking (compressed-air tacker)	

The tolerance for cross section mass, longitudinal dimensions as well as distortion and bend corresponds RAL-RG 432.

Skirting (MDF)

Parameter	Skirting	Test method
Formaldehyde Emission	E 1	EN 120
VOC-and Formaldehyde emission	A+	ISO 16000 part 3,6, 9,10
Light resistance	level 7	EN 20105
Recycling	recyclable	
Disposal	in burning plant /incinevator	
Storage	Standing or lying on an even base. Protect it from direct sunlight and moisture Climatic conditions : tempature 18°C, humidity 55-70%	

We confirm that in the manufacturing process, in the semi-finished goods and in the skirting's itself no top coating, no paints, no lacquers and no adhesives with organic solvents, biocides and free formaldehyde are used and contained.