

QUALITY MANAGEMENT ISO 9001

Code: TD_SKIRTING_WHITE_EN

Revision: 03

Date: 18.11.2020

Technical data sheet

EGGER Skirting White

Application area

Preparation of wall endings after installation of EGGER flooring

Material data

Parameter	Unit							
Surface		Melamine-/ urea impregnated decor paper						
Carrier material		MDF (medium density fibreboard)						
Product		Skirting 6 cm cubical budget	Skirting 7 cm Hamburg	Skirting 10 cm Hamburg	Skirting 4 cm cubical	Skirting 6 cm cubical	Skirting 8 cm cubical	Skirting 10 cm cubical
Profile drawing								
Length	mm	2400	2400	2400	2400	2400	2400	2400
Thickness	mm	16	18	18	16	18	18	18
Width	mm	16	70	100	40	60	80	100
Colour		White						
Paintable		Lacquering with acrylic lacquer or solvent-free lacquers before installation is recommended						
Method of use		<ul style="list-style-type: none"> • adhesive (SMP construction adhesive or 1K PU adhesive) • tacking (compressed-air tacker) • Tape strips only with adhesive tapes that do not exceed an adhesive force of 2N/ cm according to DIN EN 1939 						

Standard data

Parameter		Test method
Formaldehyde Emission	E 1	EN 120
VOC-and Formaldehyde emission	A+	ISO 16000 part 3,6,9, 10
Light resistance	level 7	EN 20105
Recycling	recyclable	
Disposal	in burning plant/ incinevator	
Cleaning	Using a vacuum cleaner With detergent pH < 8 and a damp cloth Avoid heavy accumulations of water	
Storage	Standing or lying on an even base. Protect it from direct sunlight and moisture Climatic conditions: tempature 18°C, humidity 55 - 70 %	

Logistic parameters

Description	Parameter	Skirting 6 cm cubical budget	Skirting 7 cm Hamburg	Skirting 10 cm Hamburg	Skirting 4 cm cubical	Skirting 6 cm cubical	Skirting 8 cm cubical	Skirting 10 cm cubical
Details package	Quantity	8	8	6	10	10	8	6
	Linear meter	19,2	19,2	14,4	24	24	16,2	14,4
	Dimensions [mm]	2.420 x 183 x 66	2.410 x 135 x 75	2.410 x 105 x 111	2.410 x 76 x 82	2.410 x 105 x 95	2.410 x 162 x 95	2.410 x 105 x 111
	Weight [kg] +/- 10 %	13,90	12,90	13,90	9,5	11,5	16,5	13,90
Details pallet	Quantity	320	210	280	700	350	240	210
	Linear meter	786	504	672	1680	840	567	507
	Dimensions [mm]	2.450 x 800 x 659	2.450 x 800 x 660	2.450 x 800 x 690	2.450 x 800 x 710	2.450 x 800 x 710	2.450 x 800 x 610	2.450 x 800 x 690
	Weight [kg] +/- 10 %	590	470	503	676	432	515	503

The tolerance for cross section mass, longitudinal dimensions as well as distortion and bend corresponds RAL-RG 432.

Only use adhesive tapes that do not exceed an adhesive force (according to DIN EN 1939) of 2N/cm.

We confirm that in the manufacturing process, in the semi-finished goods and in the skirting's itself no top coating, no paints, no lacquers and no adhesives with organic solvents, biocides and free formaldehyde are used and contained.

Information

All above mentioned values were determined under laboratory conditions and defined laboratory materials and structures and may with different system flooring components deviate from these test values. For all of the mentioned performance values inaccuracies are possible owing to the testing methods.

The information given above is based on our current state of knowledge and should be used for information of our product application. This should not be taken to as an assurance of certain quality of our products or their use for specific purposes. Subject to change, legal obligations cannot be derived from the information in this document. Existing commercial protective rights are to be observed.

A note on validity

This technical data sheet has been carefully drawn up to the best of our knowledge. It is intended for information only and does not constitute a guarantee in terms of product properties or suitability for specific applications. We accept no liability for any mistakes, errors in standards, or printing errors. In addition, technical changes may result from the further development of EGGER accessories as well as changes to standards and public law documents. This technical data sheet is not an instruction for use and is not a legally binding document.