

Management de la qualité ISO 9001

Codification : TL Laminat FR

ID1832


Révision : 10

Validation : 26/03/ 2021

Page : 1 sur 4

Fiche technique

Sous-couches recommandées pour sols stratifiés EGGER



Les sous-couches doivent présenter une épaisseur comprise entre 1,5 et 3,0 mm et une résistance à la pression CS \geq 10 kPa (la valeur recommandée pour des performances optimales est de 60 kPa)

Sous-couches (marque / modele) recommandées

| Fabricant ou distributeur | Sous-couche | Epaisseur mm | CLIC it! | | JUST clic! | | UNI fit! | |
|---------------------------|---------------------------------|--------------|----------|---|------------|---|----------|--|
| | | | | | | | | |
| EGGER | Silenzio Easy | 2,0 | ✓ | ✓ | ✓ | ✓ | ✓ | |
| EGGER | Silenzio Easy SD | 2,0 | ✓ | ✓ | ✓ | ✓ | ✓ | |
| EGGER | Silenzio DUO | 1,5 | ✓ | ✓ | ✓ | ✓ | ✓ | |
| EGGER | Silenzio Cork | 2,0 | ✓ | ✓ | ✓ | ✓ | ✓ | |
| Selit | Selitbloc | 1,5 | ✓ | ✓ | ✓ | ✓ | ✓ | |
| Selit | Ökolit - Kork | 2,0 | ✓ | ✓ | ✓ | ✓ | ✓ | |
| Selit | Selit-Pro Aqua Stop | 2,0 | ✓ | ✓ | ✓ | ✓ | ✓ | |
| Selit | Selitac | 2,2 | ✓ | ✓ | ✓ | ✓ | ✓ | |
| Selit | Selitac | 5,0 | ✓ | ✗ | ✓ | ✗ | ✗ | |
| Selit | Selitac Aqua Stop | 5,0 | ✓ | ✗ | ✓ | ✗ | ✗ | |
| Selit | Axton - laminate combi underlay | 2,0 | ✓ | ✓ | ✓ | ✓ | ✓ | |
| Sekisui Alveo | ALVEO Professional 140 | 1,5 | ✓ | ✓ | ✓ | ✓ | ✓ | |
| Sekisui Alveo | ALVEO PRO+ SOUNDPROTECT+ ultra | 2,0 | ✓ | ✓ | ✓ | ✓ | ✓ | |
| Sekisui Alveo | ALVEO Professional Maximum | 2,0 | ✓ | ✓ | ✓ | ✓ | ✓ | |

| Fabricant ou distributeur | Sous-couche | Epaisseur mm | CLIC it! | | JUST clic! | |
|---------------------------|---|--------------|----------|---|------------|---|
| | | | | | | |
| Ewifoam | Vinclic Professional PU | 1,6 | ✓ | ✓ | ✓ | ✓ |
| Ewifoam | Vinlay Professional SK | 2,1 | ✓ | ✓ | ✓ | ✓ |
| Ewifoam | Duogard Maxima | 2,0 | ✓ | ✓ | ✓ | ✓ |
| Ewifoam | Duogard Maxima Aquastop | 2,0 | ✓ | ✓ | ✓ | ✓ |
| Ewifoam | Silenzia Standard | 2,0 | ✓ | ✗ | ✓ | ✗ |
| Ewifoam | Silenzia Classic | 3,0 | ✓ | ✗ | ✓ | ✗ |
| Ewifoam | Silenzia Classic Aquastop Smart | 3,0 | ✓ | ✗ | ✓ | ✗ |
| Ewifoam | Universol 1000 | 1,5 | ✓ | ✓ | ✓ | ✓ |
| Ewifoam | Universol Alu classic | 2,6 | ✓ | ✓ | ✓ | ✓ |
| Ewifoam | Polytex Aquastop Smart | 1,6 | ✓ | ✗ | ✗ | ✗ |
| Ewifoam | Duogard Professional | 2,2 | ✓ | ✓ | ✓ | ✓ |
| Ewifoam | Duogard strong | 2,0 | ✓ | ✓ | ✓ | ✓ |
| PCI Thomsit | Thomsit TF302 | 2,0 | ✓ | ✓ | ✓ | ✓ |
| PCI Thomsit | Thomsit TF303 | 3,0 | ✓ | ✓ | ✓ | ✓ |
| Arbiton | Secura | 3,0 | ✓ | ✗ | ✓ | ✗ |
| WPT | SRL Solid Viscious Gummimatte | 1,7 | ✓ | ✓ | ✓ | ✓ |
| WPT | Natural Sound Basic SD PU mit Alubeschichtung | 2,2 | ✓ | ✓ | ✓ | ✓ |
| WPT | Natural Sound Comfort SD PU mit Alubeschichtung | 3,0 | ✓ | ✓ | ✓ | ✓ |
| Pregis | LBPE Black + PEE | 1,3 | ✓ | ✓ | ✓ | ✓ |
| Steico | Holzfaserdämmplatte | 2,5 | ✓ | ✗ | ✓ | ✗ |
| Dinamik-Izmir | Dyna Foam | 3,0 | ✓ | ✓ | ✓ | ✓ |
| Stiroleks | Stiroleks XPS | 3,0 | ✓ | ✓ | ✓ | ✓ |
| Ebeco | Ebisol | 3,0 | ✓ | ✗ | ✓ | ✗ |



| Fabricant ou distributeur | Sous-couche | Epaisseur mm | CLIC it! | | JUST clic! | |
|---------------------------|---------------------------------------|--------------|----------|---|------------|---|
| | | | | | | |
| | | | | | | |
| Taiga | Soundblocker Foam | 3,0 | ✓ | ✓ | ✓ | ✓ |
| Nostra | Nostrasonic Alu EVA mit ALU PET | 3,0 | ✓ | ✗ | ✓ | ✗ |
| Nostra | Nostrasonic Alu EVA mit ALU PET | 2,0 | ✓ | ✗ | ✓ | ✗ |
| Wallmann | No Noise (Warm, silent and stable) | 3,0 | ✓ | ✗ | ✓ | ✗ |
| Kraiburg Relatec | Damtec® Standard | 3,0 | ✓ | ✓ | ✓ | ✓ |
| Southafrica | Whisper LAY - beschichtete Gummimatte | 2,0 | ✓ | ✓ | ✓ | ✓ |
| Parquet Directo | Eva Gold Lamina | 2,0 | ✓ | ✓ | ✓ | ✓ |
| Maxeda (Mac Lean) | Sencys Faltmatte grau | 3,0 | ✓ | ✓ | ✓ | ✓ |
| Maxeda (Mac Lean) | Sencys isotac | 5,0 | ✓ | ✗ | ✓ | ✗ |
| MCD | Indicoustic sol | 2,0 | ✓ | ✗ | ✓ | ✗ |
| MCD | Indicoustic sol PV Plus | 3,0 | ✓ | ✗ | ✓ | ✗ |
| MSD | Indicoustic sol PV Ultra | 2,0 | ✓ | ✓ | ✓ | ✓ |
| Amorin | Rollenkork | 2,0 | ✓ | ✓ | ✓ | ✓ |
| Winoe/ Windmöller | Sound Protect Eco SD | 2,0 | ✓ | ✓ | ✓ | ✓ |
| Repac/ 4 Floor | Acoustic Board | 1,8 | ✓ | ✓ | ✓ | ✓ |
| Repac/ 4 Floor | Acoustic Tech | 1,3 | ✓ | ✓ | ✓ | ✓ |
| Repac/ 4 Floor | Acoustic LVT | 1,0 | ✓ | ✓ | ✓ | ✓ |
| Repac/ 4 Floor | XPS Rolle | 2,0 | ✓ | ✓ | ✓ | ✓ |
| Repac/ 4 Floor | Rollenkork | 2,0 | ✓ | ✓ | ✓ | ✓ |
| Austrotherm | PE 2/200 Schwerschäum | 2,2 | ✓ | ✓ | ✓ | ✓ |
| Repac | XPS Platte grau | 3,0 | ✓ | ✓ | ✓ | ✓ |



MORE FROM WOOD.

Bien plus que du bois



| Fabricant ou distributeur | Sous-couche | Epaisseur mm | CLIC it!  | JUST clic!  PATENTED EP1441287, EP1441287 | JUST clic!  PATENTED EP1441287, EP1441287 | |
|---------------------------|---------------------------|--------------|---|--|---|---|
| | | |  |  |  |  |
| Opti-Step | Sealed Air Opti-Step 3000 | 1,2 | ✓ | ✓ | ✓ | ✓ |

Remarque sur le caractère provisoire du contenu :

Les présents conseils de traitement ont été établis avec soin et en toute conscience et loyauté. Les informations ici présentées s'appuient sur l'expérience pratique ainsi que sur les essais effectués en interne. Elles correspondent à l'état actuel de nos connaissances. Elles ont un caractère informatif et ne sont en aucun cas l'assurance de caractéristiques spécifiques du produit ou de son aptitude à des applications précises. Sous réserve de fautes, d'erreurs d'impression ou de norme. Du fait de l'évolution continue des produits EGGGER Flooring, des normes et des documents légaux, certains paramètres techniques peuvent évoluer. Pour ces raisons, le contenu de la présente fiche technique ne peut être utilisé comme notice d'utilisation, ni servir de document à valeur juridique. Nos conditions générales de vente s'appliquent à ce produit.



Responsable : Technical Customer Service