

TECHNICAL DATASHEET		
EGGER PRO COMFORT		Classic
Coreboard	E1 HCHO	HDF swell stopp plus
Profil	UNI fit! LOCKING	The patented UNI fit! installation system stands for a quick and simple installation process without glue. Produced under the licence of Flooring Industries™.
Guarantee domestic area	20	according to Egger Guarantee
Guarantee comercial area	5	according to Egger Guarantee
Antistatic properties according EN1815	Antistatic	not available
Class of use		32
European Norm		EN 16511-32
Format		CLASSIC
Dimension mm (length x width)		1292 x 193
Complete thickness		10
Integrated underlay		yes, made from natural cork
Bevel		WV4
		Packaging
Pallet		One-way-pallet
Paket information		
	Piece	7
	m2	1,75
	kg	14,22
Pallet information		
	Piece	336
	m2	83,78
	kg	702,00
Classification and general requirements according to EN16511:2014		
abrasion resistance according EN13329, Annex E		AC4 (IP ≥ 1200)
impact resistance according EN13329, Annex F		≥ 1200 mm
resistance to staining EN 438 - 2		group 1 + 2: level 5 group 3: level 4
Thickness swelling according ISO 24336		≤ 18 %
tolerance of top layer according ISO 24337		length ± 0,5 mm width ± 0,1 mm thickness ± 0,5 mm
Static indentation by constant pressure according EN24343-1 (EN/ISO)		≤ 0,2
Effect of a castor chair according EN425		25.000 cycles
Thermal resistance according to EN 12667		0,09m2 K/W
Impact Sound Reduction according to EN ISO 10140 -3		≤16 dB
Room Sound Reduction IHD W 431		43% (1)
micro scratch resistance EN16094		≤MSR-A3e

* reference flooring construction: 7 mm laminate flooring on 3 mm PE-Foam and 0,2 mm PE-Film
The determined room sound improvement gives the percentage reduction of the loudness feeling relating to the reference.



TECHNICAL DATASHEET		
EGGER PRO COMFORT		Large
Coreboard	E1 HCHO	HDF swell stopp plus
Profil	UNI FIT PROFIL	The patented UNI fit! installation system stands for a quick and simple installation process without glue. Produced under the licence of Flooring Industries™.
Guarantee domestic area	20	according to Egger Guarantee
Guarantee comercial area	5	according to Egger Guarantee
Antistatic properties according EN1815	4	not available
Class of use	32	
European Norm	EN 16511-32	
Format	Large	
Dimension mm (length x width)	1292 x 245	
Complete thickness	10	
Integrated underlay	yes, made from natural cork	
Bevel	WV4	
Packaging		
Pallet	One-way-pallet	
Paket information		
	Piece	7
	m2	2,22
	kg	18,09
Pallet information		
	Piece	273
	m2	86,42
	kg	725,00
Classification and general requirements according to EN16511:2014		
abrasion resistance according EN13329, Annex E	AC4 (IP ≥ 1200)	
impact resistance according EN13329, Annex F	≥ 1200 mm	
resistance to staining EN 438 - 2	group 1 + 2: level 5 group 3: level 4	
Thickness swelling according ISO 24336	≤ 18 %	
tolerance of top layer according ISO 24337	length ± 0,5 mm width ± 0,1 mm thickness ± 0,5 mm	
Static indentation by constant pressure according EN24343-1 (EN/ISO)	≤ 0,2	
Effect of a castor chair according EN425	25.000 cycles	
Thermal resistance according to EN 12667	0,09m2 K/W	
Impact Sound Reduction according to EN ISO 10140 -3	≤16 dB	
Room Sound Reduction IHD W 431	43% (1)	
micro scratch resistance EN16094	≤MSR-A3e	

* reference flooring construction: 7 mm laminate flooring on 3 mm PE-Foam and 0,2 mm PE-Film
The determined room sound improvement gives the percentage reduction of the loudness feeling relating to the reference.



TECHNICAL DATASHEET		
EGGER PRO COMFORT		Kingsize
Coreboard		HDF swell stopp plus
Profil		The patented UNI fit! installation system stands for a quick and simple installation process without glue. Produced under the licence of Flooring Industries™.
Guarantee domestic area		according to Egger Guarantee
Guarantee comercial area		according to Egger Guarantee
Antistatic properties according EN1815		not available
Class of use		32
European Norm		 EN 16511-32
Format		Kingsize
Dimension mm (length x width)		1292 x 327
Complete thickness		10
Integrated underlay		yes, made from natural cork
Bevel		WV4
		Packaging
Pallet		One-way-pallet
Paket information		
	Piece	5
	m2	2,11
	kg	17,49
Pallet information		
	Piece	200
	m2	84,50
	kg	750
Classification and general requirements according to EN16511:2014		
abrasion resistance according EN13329, Annex E		AC4 (IP ≥ 1200)
impact resistance according EN13329, Annex F		≥ 1200 mm
resistance to staining EN 438 - 2		group 1 + 2: level 5 group 3: level 4
Thickness swelling according ISO 24336		≤ 18 %
tolerance of top layer according ISO 24337		length ± 0,5 mm width ± 0,1 mm thickness ± 0,5 mm
Static indentation by constant pressure according EN24343-1 (EN/ISO)		≤ 0,2
Effect of a castor chair according EN425		25.000 cycles
Thermal resistance according to EN 12667		0,09m2 K/W
Impact Sound Reduction according to EN ISO 10140 -3		≤16 dB
Room Sound Reduction IHD W 431		43% (1)
micro scratch resistance EN16094		≤MSR-A3e

* reference flooring construction: 7 mm laminate flooring on 3 mm PE-Foam and 0,2 mm PE-Film
The determined room sound improvement gives the percentage reduction of the loudness feeling relating to the reference.

