







## TECHNICAL DATASHEET

Egger Home Laminate Flooring

7/ 31 WV4

Coreboard		HDF swell stopp plus
Profile		The patented EGGER installation system JUST clic! stands for quick and simple installation process without glue. Patented as JUST clic! EP 1 441 087 and EP 1 462 587
Guarantee domestic area		according to Egger Guarantee
Guarantee comercial area		according to Egger Guarantee
Antistatic properties according EN1815		yes, < 2 kV
Class of use	<b>31</b>	
European Norm EN13329	 EN 13329-31	
Format	<b>CLASSIC</b>	
Dimension mm (length x width)	<b>1292 x 192</b>	
Complete thickness	<b>7</b>	
Thickness of silenzio® special cellulose		
Bevel	<b>WV4</b>	
Profil	<b>JUST clic!</b>	
Packaging	<b>Packaging</b>	
Pallet	<b>Euro</b>	
<b>Paket information</b>		
	Piece	10
	m2	2,48
	kg	15,63
<b>Pallet information</b>		
	Piece	520
	m2	128,99
	kg	826,00
<b>Classification and general requirements according EN13329</b>		
Abrasion resistance according EN13329, annex E	AC3 (IP ≥ 2000)	
Impact resistance according EN13329, annex H	Big ball: ≥ 500 mm Small ball: ≥ 8 N	
Resistance to staining EN438	Group 1 + 2: level 5 group 3: level 4	
Effect of furniture leg according EN424	No damage shall be visible, when tested with foot Type 0 artefact	
Effect of a castor chair according EN425 (Type W)	No change in appearance or damage	
Thickness swelling according ISO 24336	≤ 18 %	
Tolerance of top layer according EN13329	length ± 0,5 mm width ± 0,1 mm thickness ± 0,5 mm	
Light fastness according EN13329	grey scale ≥ level 4 (EN:20105-A02)	
Static indentation by constant pressure according EN ISO 24343-1	< 0,05	
Surface soundness according EN13329, annex D	≥ 1,0 N/mm <sup>2</sup>	
Thermal resistance according to EN 12667	0,06 m <sup>2</sup> K/W	

