

Code: SDS-PerfectSense-EN
 Version: 00
 Release Date: 27.02.2018

Safety Data Sheet

EGGER Perfect Sense

According to 29 CFR 1910.1200 App D

This product is not hazardous in the form in which it is shipped by the manufacturer, but may become hazardous by wood dust generating downstream activities (e.g. grinding, sanding, cutting or pulverizing).

Section 1: Identification of the substance/mixture and the company/undertaking

1.1 Product Identifier

Trade name PerfectSense gloss/matt lacquered boards
 Medium density fiberboard, PerfectSense
 Product description Melamine resin coated MDF boards, with CCI UV coating technology

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use Kitchen fronts, bathroom furniture, interior design, sliding door elements

1.3 Details of the supplier of the Safety Data Sheet

Manufacturer/Supplier/Importer Fritz EGGER GmbH & Co. OG
 Weiberndorf 20
 6380 St. Johann in Tyrol
 Austria
 +43 0800 888 111
 Regional Support Centre EGGER Wood Products LLC(US)
 P.O. Box 907
 Lexington, NC 27293
 T+1-800-940-9633

1.4 Emergency phone number

1-800-424-9300 / +1 703-527-3887 (Chemtrec)

Section 2: Hazards identification


2.1 Classification of the substance or mixture

OSHA HCS 2012 This product is generally an article and not hazardous, but is regulated under OSHA for the release of wood dust during downstream activities, like grinding, sanding, cutting and sawing. The free formaldehyde levels are below OSHA reporting requirements. The classifications below are based upon wood dust:
 Skin Irritation 2
 Skin Sensitization 1
 Eye Mild Irritation 2B
 Respiratory Sensitization 1
 Specific Target Organ Toxicity Repeated Exposure 2: Respiratory Tract Irritation
 Carcinogenicity 1A
 Combustible Dust

2.2 Label elements

Labelling according to paragraph (f) 1910.1200; OSHA29 CFR

Hazard pictograms



Signal word

DANGER

Hazard statements

May form combustible dust concentrations in air
 H315 Causes skin irritation
 H317 May cause an allergic skin reaction
 H320 Causes eye irritation
 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled
 H335 May cause respiratory irritation
 H350 May cause cancer (inhalation)
 H373 Causes damage to organs through prolonged or repeated exposure (inhalation)

Precautionary statements

P202 Do not handle until all safety precautions have been read and understood
 P210 Keep away from heat/sparks/open flames/hot surfaces – no smoking
 P260 Do not breathe dust
 P271 Use only outdoors or in a well-ventilated area
 P280 Wear protective gloves/protective clothing/eye protection
 P302+P352+P305+P351+P338 On contact: Wash thoroughly with water
 P308+P337+P314+P340+ P264 If exposed or concerned: Get medical advice/attention if you feel unwell, move to fresh air

2.3 Other hazards

Results of PBT and vPvB assessment

PBT

Not applicable

vPvB

Not applicable

OSHA HCS 2012

This product is not considered hazardous under the U.S. OSHA 29 CFR 1910.1200 Hazard Communication Standard in the form in which it is shipped, but may become hazardous by wood dust generating downstream activities (e.g. grinding, sanding, cutting or pulverizing).

NFPA

Health=1, Flammability=1, Reactivity=0, Special Information=None

HMIS

Health=1*, Flammability=1, Reactivity=0, PFE=E

*Chronic Health Hazard

E=Safety glasses, gloves, and a dust respirator

Section 3: Composition/information on ingredients

3.2 Chemical characterization: Mixtures

Description

The products are composed of wood and cured amino resins. See Section 8 for exposure limits discussion.

Components shown below may appear in some or in various combinations in a particular product. With the exception of Formaldehyde, only components above the appropriate cut-off limit are shown.

Composition MDF raw board

Chemical Name	Identifiers	%	Hazardous
Wood fibers*	CAS: not applicable	approx. 82%	YES
Water	CAS: 7732-15-5	5% to 7%	NO
UMF-resins (cured)	CAS: not applicable	approx. 11%	NO
Paraffin-wax emulsion	CAS: not applicable	<1%	NO
Formaldehyde (free)	CAS: 50-00-0	<0,1%	YES

The raw MDF is covered with melamine impregnated paper and lacquer based on acrylic acid. In the finished products the resin and the lacquer is cured.

*Wood contains trace amounts of various chemicals present in the environment, which are absorbed by trees through natural growth. A comprehensive listing of species is available upon request.

All products produced at EGGER are certified according to the strict California Air Resources Board (CARB)/ TSCA Title VI CALIFORNIA RESIDENTS: This product contains one or more chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm.

Section 4: First aid measures

4.1 Description of first aid measures

General information	No special measures required
Inhalation	If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
Skin	Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. After contact with the molten product, cool rapidly with cold water
Eye	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	Rinse mouth thoroughly with water. Get medical attention if you feel unwell and contact a poison control center or medical professional.

4.2 Most important symptoms and effects, both acute and delayed

Refer to Section 11 – Toxicological Information

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available

Section 5: Firefighting measures

5.1 Extinguishing media

Use firefighting measures that suit the environment

Water

Fire-extinguishing powder

Carbon dioxide

Foam

5.2 Special hazards arising from the substance or mixture

Medium density fiberboard s are a Class A combustible material. If involved in a fire, product will burn.

Medium density fiberboard s are not an explosion hazard. Sawing, sanding, or machining medium density fiberboards can result in the by-product wood dust. Wood dust may present a strong to severe explosion hazard if a dust cloud contacts an ignition source.

Airborne concentrations of 15 grams per cubic meter are often used as the lower explosive limit (LEL) for wood dusts.

OSHA interprets the explosive level as having no visibility within five feet or less.

In case of fire, the following gases can be released:

Carbon dioxide (CO₂), Carbon monoxide (CO), Oxides of Nitrogen, Aldehydes, Cyanides and other hazardous gases and particles

5.3 Advice for firefighters

Protective equipment Mouth respiratory protective device

Additional information Prevent formation of dust

Dispose of fire debris and contaminated firefighting water in accordance with official regulations.

Section 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal Precautions Do not breathe dust.
 Emergency Procedures No emergency procedures are expected to be necessary if material is used under ordinary conditions as recommended.

6.2 Environment precautions

No special measures required

6.3 Methods and material for containment and cleaning up

Not applicable for product in purchased form. Dust generated from sawing, sanding, drilling or routing this product may be vacuumed or shoveled for recovery or disposal. Wood dust clean-up and disposal activities should be accomplished in a manner to minimize of airborne dust.

Dispose of the material collected according to regulations

6.4 Reference to other sections

See Section 7 for information on safe handling
 See Section 8 for information on personal protection equipment
 See Section 13 for disposal information

Section 7: Handling and storage

7.1 Precautions for safe handling

Use good safety and industrial hygiene practices. Minimize dust generation and accumulation. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces. Wear a respiratory mask if using hand tools without a dust extraction device. Observe all liability insurance association regulations for commercial processing operations (e.g. safety goggles).

Information on protection against explosions and fires

Avoid formation of dust

7.2 Conditions for safe storage, including any incompatibilities

Storage No special precautions for handling product. Use good safety and industrial hygiene practices. Minimize dust generation and accumulation. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces.
 Keep away from ignition sources

7.3 Specific end use(s)

No further relevant information available

Section 8: Exposure controls/personal protection

8.1 Control parameters

Wood dust needs to be controlled while cutting, sawing, drilling or other dust generating processes are performed.

8.2 Exposure controls

	Result	ACGIH 2007	NIOSH	OSHA
Wood dust	TWAs	1mg/m ³ TWA As Wood dust , all soft and hard woods	1mg/m ³ TWA As Wood dust, all soft and hard woods	15mg/m ³ , total dust(5mg/m ³ , respirable fraction) (as nuisance dust)
Formaldehyde (50-00-0)	TWAs	0,3ppm TLV	0,016ppm TWA, 0.1ppm Ceiling (15 minutes)	0,75ppm TWA, 2ppm STEL, 0.5ppm action level

Engineering measures/ controls

Adequate ventilation systems as needed to control concentrations of airborne contaminants below applicable threshold limit values. Due to the explosive potential of wood dust when suspended in air, precautions should be taken during sanding, sawing or machining of wood products to prevent sparks or other ignition sources in ventilation equipment. Use of totally enclosed motors is recommended.

Personal Protective Equipment Pictograms



Respiratory

Eye/Face
Hands

Skin/Body
General Industrial Hygiene Considerations

Environmental Exposure Controls

Use of a NIOSH/MSHA approved dust respirator is recommended where airborne dust levels exceed appropriate PELs and TLVs
 Wear safety glasses
 Wear protective gloves – Rubberized cloth, canvas or leather gloves
 Wear long sleeves and/or protective coveralls.
 Practice good housekeeping and avoid creating/breathing dust. Do not allow dust to collect. Maintain, clean, and fit test respirators in accordance with OSHA regulations.
 No data available

Section 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical State	Solid	Evaporation rate	Not relevant
Color	Varies	Partition coefficient	Not relevant
Flammability	D-s2, d0 (EN 13501-1)	Autoignition	No data available
Odor	No distinctive odor	Decomposition Temperature	No data available
Vapor Pressure	Not relevant	Viscosity	No data available
Odor threshold	Not relevant	Burning time	No data available
Vapor Density	No data available	Density (raw board)	approx. 700kg/m ³ (EN323)
pH	Not relevant	Oxidizing properties	No data available
Relative density	Not relevant	Explosive limits	No data available
Melting point	Not relevant	Flash point	Not relevant
Freezing Point	Not relevant	Boiling Point	Not relevant
Solubility	Not soluble in water		

9.2 Other information

No further relevant information available.

Section 10: Stability and reactivity

10.1 Reactivity

The product is not reactive under normal conditions of use, storage and transport.

10.2 Chemical stability

Stable under recommended storage conditions

Conditions to be avoided: No decomposition if used according to specifications

10.3 Possibility of hazardous reactions

No dangerous reactions known

10.4 Conditions to avoid

Exposure to water, ignition source, high relative humidity and high temperature

10.5 Incompatible materials

Incompatible Materials: acids(strong), Oxidizers(strong)

10.6 Hazardous decomposition products

Hazardous decomposition may occur thermal and/or thermal oxidative decomposition can produce irritating and toxic fumes and gases, generating carbon oxides, HCN, aldehydes and organic acids.

Section 11: Toxicological information

11.1 Information on toxicological effects

Other Material Not applicable for product in purchased from. Individual component information is provided below if available

Components
Formaldehyde 50-00-0 Acute Toxicity: Ingestion/Oral-Rat LD50 >200mg/kg; Inhalation-Rat LD50 0,578mg/l/4h;

GHS Properties	Classification
Acute toxicity	OSHA HCS 2012 – Acute Toxicity – Data lacking (Oral, dermal, inhalation)
Aspiration hazard	OSHA HCS 2012 – Data lacking
Carcinogenicity	OSHA HCS 2012 -- Carcinogenicity 1A
Germ Cell Mutagenicity	OSHA HCS 2012 – Data lacking
Skin corrosion/Irritation	OSHA HCS 2012 – Skin Irritation 2
Skin sensitization	OSHA HCS 2012 – Skin Sensitizer1
STOT-RE	OSHA HCS 2012 – Specific target Organ Toxicity Repeated Exposure 2
STOT-SE	OSHA HCS 2012 – Specific target Organ Toxicity Single Exposure 3: respiratory Tract Irritation
Toxicity for Reproduction	OSHA HCS 2012 – Data lacking
Respiratory sensitization	OSHA HCS 2012 – Respiratory Sensitizer 1
Serious eye damage/Irritation	OSHA HCS 2012 – Eye Mild Irritation 2B

Target Organs Skin/dermal. Lungs, Respiratory System
Route(s) of entry/exposure Inhalation, Skin, eye
Medical Conditions Dusts may aggravate asthma or other respiratory disorders.
Aggravated by Exposure

Potential Health Effects

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs include:

Inhalation

Acute(Immediate) May cause respiratory irritation
Chronic (Delayed) Repeated and prolonged exposure may cause cancer. Repeated and prolonged exposure may cause sensitization of the respiratory system.

Skin

Acute(Immediate) May cause irritation
Chronic(Delayed) Repeated and prolonged exposure may cause sensitization

Eye

Acute (Immediate) May cause irritation
Chronic(Delayed) No data available

Ingestion

Acute(Immediate) Under normal conditions of use, no health effects are expected.
Chronic(Delayed) Under normal conditions of use, no health effects are expected.
Carcinogenic Effects Wood dust is listed by NTP known to be a Human Carcinogen(10th Report), IARC Monographs: Wood dust, group 1 – IARC Group 1: Carcinogenic to humans; sufficient evidence of carcinogenicity. This classification is primarily baes on studies showing an association between occupational exposure to wood dust and adenocarcinoma of the nasal cavities and paranasal sinuses. IARC di d not find sufficient evidence of an association between occupational exposure to wood dust and cancers of the hypopharynx, oropharynx, lymphatic and hematopoietic systems, lungs, stomach, colon or rectum.

Carcinogenic Effects

	CAS	OSHA	IARC	NTP
Wood dust as Wood dust, all soft and hard woods	Not Available	Not Listed	Group 1-Carcinogenic	Known Human Carcinogen
Formaldehyde	50-00-0	Specifically Regulated Carcinogen	Group 1 – Carcinogenic	Known Human Carcinogen

Section 12: Ecological information

12.1 Toxicity

Formaldehyde: EC50 5,8mg/l/48h (Daphnia magna)

Not applicable for medium density fiberboard

12.2 Persistence and degradability

No further relevant information available

12.3 Bioaccumulative potential

Formaldehyde: log P_{ow} 0,35

Not applicable for medium density fiberboard

12.4 Mobility in soil

No further relevant information available

General notes

Generally not hazardous for water

12.5 Results of PBT and vPvB assessment

PBT

Not applicable

vPvB

Not applicable

12.6 Other adverse effects

No further relevant information available

Section 13: Disposal considerations

13.1 Waste treatment methods

Recommendation Disposal according to local regulations

Uncleaned packaging

Recommendations Dispose of packaging according to regulations on the disposal of packaging

Section 14: Transport information

14.1 UN-number

ADR, ADN, IMDG, IATA

Void

14.2 UN proper shipping name

ADR, ADN, IMDG, IATA

Void

14.3 Transport hazard class(es)

ASR, ADN, IMDG, IATA class

Void

14.4 Packing group

ADR, IMDG, IATA

Void

14.5 Environmental hazards

Not applicable

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

UN "Model Regulation"

void

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

SARA Hazard Classifications

Acute, Chronic

Inventory

Component	CAS	Canada DSL	TSCA
Medium density fiberboard	Not applicable	Not listed. All components are on the Canada DSL or are excluded from listing	Not listed. All components are on the TSCA inventory or are excluded from listing.

Canada – WHMIS – Classifications of Substances
Medium density fiberboards and ingredients (unless listed below)

N/A

Not listed or below de minimis reporting quantities

Formaldehyde Canada – WHMIS – Ingredient Disclosure List	50-00-0	B1, D1A, D2A, D2B
Medium density fiberboard and ingredients(unless listed below)	N/A	Not listed or below de minimis reporting quantities
Formaldehyde	50-00-0	0,1% (concentration in product is below de Minimis)
U.S.-OSHA – Process Safety Management – Highly hazardous Chemicals		
Medium density fiberboard and ingredients (unless listed below)	N/A	Not listed
Formaldehyde Environment	50-00-0	1000lb TQ
U.S. – CERCLA – Hazardous Substances		
Medium density fiberboard and ingredients(unless listed below)	N/A	Not listed
Formaldehyde	50-00-0	100lb final RQ
U.S. – CERCLA/SARA – Section 304 EHS RQ		
Medium density fiberboard and ingredients(unless listed below)	N/A	Not listed
Formaldehyde	50-00-0	100lb EPCRA RQ
U.S. – EPCRA –Section 302 (EHS) TPQ		
Medium density fiberboard and ingredients(unless listed below)	N/A	Not listed
Formaldehyde	50-00-0	500lb TPQ
U.S. – EPCRA – Section 313 – Toxic Chemicals		
Medium density fiberboard and ingredients(unless listed below)	N/A	Not listed
Formaldehyde	50-00-0	0.1% de Minimis concentration(Concentration in product is below de Minimis)
United States – California Environment		
U.S. – California – Proposition 65 –Carcinogens List		
Medium density fiberboard and ingredients(unless listed below)	N/A	Not listed
Formaldehyde (gas)	50-00-0	Carcinogen, NSRL 40µg/day
Wood dust as Wood dust, all soft and hard woods	N/A	Carcinogen

15.2 Chemical Safety Assessment

A Chemical Safety Assessment has not been carried out

Section 16: Other information

This information is based on our present knowledge and comes from sources believed to be accurate or otherwise technically correct. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

User alkrimba
Last Revision Date 27.02.2018

Abbreviations and acronyms

OSHA	Occupational Safety and Health Administration
HCS	Hazard Communication Standard
NFPA	National Fire Protection Association
HMIS	Hazardous Materials Identification System
TWA	Time-weighted average
STEL	Short-term exposure limit
ACGIH	Association Advancing Occupational and Environmental Health
NIOSH	National Institute for Occupational Safety and Health
PEL	Personal Exposure Limit
TLV	Threshold limit value
ADR	Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG	International Maritime Code for Dangerous Goods
IATA	International Air Transport Association
GHS	Globally Harmonized System of Classification and Labelling of Chemicals
CAS	Chemical Abstracts Service (division of the American Chemical Society)
PBT	Persistent, Bioaccumulative and Toxic
vPvB	Very Persistent and very Bioaccumulative

GHS Product Hazard Label

PerfectSense Medium density fiberboard

According to OSHA 29 CFR 1910.1200 HCS



Danger

This product is generally an article, but is regulated under OSHA for the release of wood dust during mechanical operations releasing wood dust. No adverse health effects are expected, if the product is handled in accordance with the product label and the product Safety Data Sheet. Symptoms or effects that may arise if the product is mishandled and overexposure occurs include:

Causes Skin irritation

May cause an allergic skin reaction

Causes eye irritation

May cause respiratory irritation

May cause allergy or asthma symptoms or breathing difficulties if inhaled

May cause cancer via inhalation of respirable dust

May form combustible dust concentrations in air

Causes damage to organs through prolonged or repeated exposure

Do not handle until all safety precautions have been read and understood

Keep away from heat/sparks/open flames/hot surfaces – no smoking

Do not breath dust

On contact: Wash thoroughly with water

If exposed or concerned: get medical advice/attention if you feel unwell, move to fresh air

Use only outdoors or in a well-ventilated area

Wear protective gloves/protective clothing/eye protection

IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: get medical advice/attention

Take off contaminated clothing and wash it before reuse

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. If eye irritation persists: get medical advice/attention

IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing

If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician

IF exposed or concerned: get medical advice/attention.

Store away from water and sources of ignition. It is recommended to store the product in an area with relative humidity and temperature that approximates end use conditions.

Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Fritz EGGGER GmbH & Co. OG,
Weiberndorf 20

6380 St. Johann in Tirol, Austria

General Information: +43 800 888 111

California Proposition 65 Notification Requirement

Warning

Drilling, sawing, or machining wood products generates wood dust, a substance known to the State of California to cause cancer. Avoid inhaling wood dust or use a dust mask or another safeguards for personal protection.

Fritz EGGGER GmbH & Co. OG,
Weiberndorf 20
6380 St. Johann in Tirol, Austria
General Information: +43 800 888 111